

Pot Cores (5695302021)



Part Number: 5695302021

95 POT CORE SET

Pot cores have found application in all types of inductive devices. The core configuration provides a high degree of self-shielding. It also facilitates gapping to enhance utility for a variety of magnetic designs.

Pot cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Catalog Drawing 3D Model

Weight indicated is per pair or set.

Weight: 34.000 (g)

Dim mm mm tol nominal inch inch misc. A 30 ±0.50 1.181			(8)		
B 9.4 ±0.20 0.37	Dim	mm	mm tol	nominal inch	inch misc.
C 20.6 min 0.812 min D 6.6 ±0.20 0.26 E 25 min 0.985 min F 13.3 ±0.20 0.524 G 3.68 min 0.145 min	A	30	±0.50	1.181	_
D 6.6 ±0.20 0.26	1	9.4	±0.20	0.37	
E 25 min 0.985 min F 13.3 ±0.20 0.524 G 3.68 min 0.145 min	С	20.6	min	0.812	min
F 13.3 ±0.20 0.524 G 3.68 min 0.145 min	D	6.6	±0.20	0.26	_
G 3.68 min 0.145 min	Е	25	min	0.985	min
	F	13.3	±0.20	0.524	_
H 5.6 ±0.20 0.22	G	3.68	min	0.145	min
	Н	5.6	±0.20	0.22	




Chart Legend

 Σ l/ A : Core Constant, l_e : Effective Path Length, A_e : Effective Cross- Sectional Area, V_e :

Effective Core Volume
A₁: Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties				
$A_{L}(nH)$	$7500 \pm 25\%$			
Ae(cm ²)	1.27			
$\Sigma l/A(cm^{-1})$	3.56			
l _e (cm)	4.53			
$V_e(cm^3)$	5.75			
$A_{min}(cm^2)$	1.14			

 A_r value is measured at 1 kHz, B < 10 gauss.

888-324-7748