

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

ITEM	DESCRIPTION	MATERIAL	OTHERS
1	MALE CONTACT	COPPER ALLOY	FLASH GOLD
2	HOUSING	NYLON	BLACK
3	COUPLING NUT	COPPER ALLOY	-
4	OVER-MOLDING	POLYURETHANE	BLUE
5	CABLE	-	-
6	LABEL	-	-

PIN 2-BROWN

PIN 3-GREEN

PIN 4-YELLOW

PIN 5-GRAY

PIN 6-PINK

PIN 8-RED

PIN 1-WHITE

PIN 7-BLUE

47 REF.

15 REF.

M12X1

SW13

50 REF.

35±5

"L"

0m to 1m ±0.05m

1m to 3m ±0.1m

>3m ±1.5%

NOTE:

1. STRIP AND RETAIN THE INSULATION

2. CODE POSITION INDICATOR

3. RECOMMENDED TORQUE 0.6 Nm

4. -** :CABLE LENGTH

-0.5:0.5M,

-1.0:1.0M,

-1.5:1.5M,

-3.0:3.0M,

-5.0:5.0M,

-7.0:7.0M,

-10.0:10.0M,

5. CABLE ASSEMBLY TO BE PACKAGED IN POLYBAGS

6. LABEL CONTAINS: PN, DATE CODE...

注释:

1. 剥线并保留护套绝缘层

2. CODE位置指示

3. 推荐扭矩0.6 Nm

4. -** :线缆长度

-0.5:0.5M,

-1.0:1.0M,

-1.5:1.5M,

-3.0:3.0M,

-5.0:5.0M,

-7.0:7.0M,

-10.0:10.0M,

5. 线缆组件塑料袋包装

6. 标签包含: 产品编号, 日期代码...

TECHNICAL DATA	T41611X0008-00X
RATED VOLTAGE	MAX. 30V AC/DC
RATED CURRENT	MAX. 2A
POLLUTION DEGREE	3
OVERVOLTAGE CATEGORY	II
MATERIAL GROUP	II
DEGREE OF PROTECTION	IP67(PLUGGED)

WIRES: 0.25mm^2(24AWG) WIRE COLOR: WHITE/BROWN/GREEN/YELLOWE/ GRAY/PINK/BLUE/RED OD: APPROX.6.0MM FOR 8P	STANDARD: -001:0.5M -002:1.0M -003:1.5M -004:3.0M -005:5.0M -006:7.0M -007:10.0M CUSTOMIZATION: -**0:**.0 M -**5:**.5 M	FIXED: -40°C~+80°C FLXIBLE: -25°C~+80°C	GRAY	PUR (UL)	RPC-M12-MS-8CON-PUR-**SH4	8	T4161120008-00X
		FIXED: -40°C~+80°C FLXIBLE: -25°C~+80°C	BLACK	PVC (UL)	RPC-M12-MS-8CON-PVC-**SH4	8	T4161110008-00X
	CABLE CHARACTERISTIC	LENGTH "L"	CABLE TEMP. RANGE	JACKET COLOR	JACKET MATERIAL	TYPE	POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN HAO WANG 24AUG2016

CHK KOBBY ZHAO 24AUG2016

APVD XIANG XU 24AUG2016

PRODUCT SPEC 108-106140

APPLICATION SPEC 114-137144

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:

mm

MATERIAL -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±-

2 PLC ±-

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH -

TE Connectivity

NAME M12X1 STRAIGHT PLUG, FREE END
A-CODE, 8P
SHIELDED,

SIZE A2

CAGE CODE -

DRAWING NO. T41611X000800X

RESTRICTED TO -

SCALE 2:1

SHEET 1 OF 1

REV A

1471-9 (3/13)