

### Main

Disconnecter device type	Fusible disconnect switch
Range of product	TeSys D

### Complementary

Rated current	12 A
Associated fuse rating	30 A
[Uc] control circuit voltage	120 V AC 50/60 Hz for coil circuit
Fuse type	CC
Internal voltage transformer	Without
Motor power hp	10 hp 575 V AC 7.5 hp 460 V AC 3 hp 200/230 V AC
Motor starter type	Non reversing
Overload protection	Without

### Environment

NEMA degree of protection	NEMA 12/3R
---------------------------	------------

### Offer Sustainability

WARNING: Cancer - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>	WARNING: Cancer - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
--	--

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.