

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [45593-1602](#)  
**Status:** **Active**  
**Overview:** HandyLink™ I/O Interconnect System  
**Description:** 0.80mm Pitch HandyLink™ Plug for PCB Termination, 16 Circuit (pins 2,3,4,5,6,7,8,15 voided)

**Documents:**

[3D Model](#) [Product Specification PS-44828-001 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**


CSA LR19980  
 UL E29179

**General**

Product Family I/O Connectors  
 Series [45593](#)  
 Application Board-to-Board  
 Comments Please reference Application Specification AS-44828-001 when designing  
 Component Type Plug  
 More Detailed Tech Information [handylink@molex.com](mailto:handylink@molex.com)  
 Overview [HandyLink™ I/O Interconnect System](#)  
 Product Name HandyLink®  
 Type N/A  
 UPC 756054882634

**Physical**

Circuits (Loaded) 8  
 Circuits (maximum) 16  
 Circuits Detail Terminals 1, 9, 10, 11, 12, 13, 14, 16 Loaded  
 Color - Resin Black  
 Durability (mating cycles max) 700  
 Flammability 94V-0  
 Gender Plug  
 Keying to Mating Part None  
 Lock to Mating Part Yes  
 Material - Metal High Performance Alloy (HPA), Stainless Steel  
 Material - Plating Mating Gold, Tin  
 Material - Plating Termination Tin  
 Material - Resin High Temperature Thermoplastic  
 Net Weight 5.770/g  
 Orientation Vertical  
 PC Tail Length 1.10mm  
 PCB Retention Yes  
 PCB Thickness - Recommended 1.00mm  
 Packaging Type Tray  
 Panel Mount No  
 Pitch - Mating Interface 0.80mm  
 Plating min - Mating 0.102µm, 1.270µm  
 Plating min - Termination 1.270µm, 5.080µm  
 Polarized to Mating Part Yes  
 Surface Mount Compatible (SMC) No  
 Temperature Range - Operating -40°C to +85°C  
 Termination Interface: Style Through Hole  
 Wire Size AWG N/A



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC**  
 Not Reviewed  
**Low-Halogen Status**  
 Not Reviewed

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[45593Series](#)

**Mates With**

[44828 HandyLink®#153 Receptacle](#)

**Electrical**

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	30V

**Solder Process Data**

Lead-free Process Capability	Wave Capable (TH only)
------------------------------	------------------------

**Material Info****Reference - Drawing Numbers**

Product Specification	PS-44828-001
Sales Drawing	SD-45593-001, SD-45593-3600

This document was generated on 12/23/2014

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**