## Product datasheet Characteristics

## 9013GHW5J61X



Main	
Device short name	G
Enclosure type	Weatherproof enclosure dust and damp proof indoor/outdoor
Factory modification	2-way pressure release valve
Product specific application	Control electrically driven water pumps and air compressors
Range of product	Square D Pumptrol
Switch application	Standard

## Complementary

Available

including:

WARNING: This product can expose you to chemicals

Adjustable range on rising pressure	80250 psi	
Approximate adjustable differential	4060 psi	
Depth	3.68 in	
Electrical connection	Screw clamp terminal	
Fixing mode	By brackets	
Fluid connection type	0.25 inch NPSF internal	
Height	5.72 in	
Material	Zinc plated steel flange	
Materials in contact with fluid	Nitrile (Buna-N) diaphragm	
Maximum pressure	250 psig	
Motor power hp	2 hp 115 V AC 1 phase 3 hp 230 V AC 1 phase 5 hp 230 V AC 3 phases 3 hp 115 V AC 3 phases 5 hp 460/575 V AC 3 phases 5 hp 460/575 V AC 1 phase	
Number of poles	2	
Permissible voltage	<= 575 V AC	
Pressure actuator	Diaphragm	
Pressure setting range	130175 psi	
Product weight	2.25 lb(US)	
Range on decreasing pressure	30190 psi	
Switch function	DPST	
Width	3.44 in	
Environment		
NEMA degree of protection	NEMA 4	
product certifications	UL listed file E12158 CCN NKPZ CSA file LR25490	
Offer Sustainability		
Not Green Premium product	Not Green Premium product	
Will not be Compliant	Will not be Compliant	
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold	
Available	Available	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a usbitture for and is not to be used for determining suitability of these products for specific user applications. It is the duty of any cut user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products for specific user applications. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



WARNING: This product can expose you to chemicals including:

Available

Lead and lead compounds, which is known to the State Lead and lead compounds, which is known to the State of California to cause cancer of California to cause cancer and birth defects or other and birth defects or other reproductive harm. reproductive harm.

Di-isodecyl phthalate (DIDP) which is known to the State Di-isodecyl phthalate (DIDP) which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

