

## AX101886 Modular Connectors - MediaFlex Multimedia insert 1-Port SVGA



For more Information  
please call

1-800-Belden1

**General Description:**

MediaFlex Multimedia insert 1-Port SVGA

**Usage (Overall)**

|                        |                                      |
|------------------------|--------------------------------------|
| Suitable Applications: | Multimedia                           |
| Related Parts:         | Compatible with MediaFlex Faceplates |

**Physical Characteristics (Connectivity)****Dimensions**

Dimensions:

| Height (mm) | Width (mm) | Depth (mm) |
|-------------|------------|------------|
| 35.306      | 52.070     | 35.814     |

**Materials**

Materials:

| Description      | Type | Material          |
|------------------|------|-------------------|
| Front Connection | SVGA | Metal             |
| Rear Connection  | 110  |                   |
| Insert           |      | Plastic - UL94V-0 |

**Color**

Color: Almond

**Weight**

Weight: 0.026 kg

**Included Parts**

Included Parts: pin assignment guide

**Packaging**

Packaging: Individually packaged in a suitable plastic bag.

**Mechanical Characteristics (Connectivity)**

|                                 |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|
| Storage Temperature Range:      | -40°C To +70°C                                                                      |
| Installation Temperature Range: | -10°C To +60°C                                                                      |
| Operating Temperature Range:    | -10°C To +60°C                                                                      |
| Tool Compatibility:             | Connecting Tool (AX100749), Termination Station (AX101852), Release Tool (AX101185) |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |                                  |
|---------------------------------------|----------------------------------|
| EU Directive 2002/95/EC (RoHS):       | Yes                              |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2006                       |
| MIL Order #39 (China RoHS):           | EUP 50                           |
| Safety Listing:                       | ACA, Bi-national Standard Listed |

**Suitability**

Suitability - Indoor: Yes - Indoor

**Transmission Characteristics (Connectivity)****Notes (Overall)**

**Notes:** For proper installation refer to pin assignment guide provided with the product and Installation Guide PX102063 available on our web site at <http://www.belden.com>

**Product Family**

Part Number List:

| Item Number | Color  |
|-------------|--------|
| AX101885    | Gray   |
| AX101886    | Almond |

## METRIC MEASUREMENT VERSION

### AX101886 Modular Connectors - MediaFlex Multimedia insert 1-Port SVGA

|          |                  |
|----------|------------------|
| AX101887 | Electrical White |
| AX101888 | Black            |

#### Put Ups and Colors:

| Item #   | Putup | Ship Weight | Color | Notes | Item Desc                |
|----------|-------|-------------|-------|-------|--------------------------|
| AX101886 | 1 EA  | 0.058 LB    |       |       | MEDIAFLEX SVGA IDC INSER |

Revision Number: 0    Revision Date: 06-03-2009

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.