



Main

Range of product	Integral 32
Device short name	LX1
Product or component type	Coil
[Uc] control circuit voltage	240 V AC 50 Hz
Power consumption in VA	10...16 VA AC network 50 Hz sealed (cos ϕ 0.28) 150...200 VA AC network 50 Hz inrush (cos ϕ 0.55)
Value of inductance	15.4 mH closed circuit
Average resistance	203 Ohm at 68 °F (20 °C) +/- 10 %

Complementary

Product weight	0.26 lb(US) (0.12 kg)
----------------	-----------------------

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.