9001K53J35LGFG



Main

| Range of product | Harmony 9001K |
|---------------------------|-----------------------------|
| Product or component type | Illuminated selector switch |
| Device short name | 9001K |
| Type of operator | Spring return (to centre) |
| Operator profile | Long handle green |
| | |

Complementary

| Bezel material | Chromium plated metal | |
|-------------------------------|----------------------------------|---|
| Mounting diameter | 1.18 in (30 mm) | |
| Product weight | 0.54 lb(US) (0.245 kg) | |
| Shape of signaling unit head | Octagonal | |
| Operator position information | 3 positions | |
| Contacts type and composition | Without contact block | _ |
| Mechanical durability | 500000 cycles | _ |
| Light block supply | Direct | |
| Light source | LED | |
| Bulb base | BA 9s | |
| Light block colour | Green | |
| [Us] rated supply voltage | 24 V AC/DC | |
| Product compatibility | 9001KA1, mounting on side 1 or 2 | |
| Device presentation | Basic element | |

| Environment | | |
|---------------------------------------|--|--|
| protective treatment | TC | |
| ambient air temperature for storage | -40158 °F (-4070 °C) | |
| ambient air temperature for operation | -13158 °F (-2570 °C) | |
| electrical shock protection class | Class II conforming to IEC 61140 | |
| IP degree of protection | IP66 conforming to IEC 60529 | |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 | |
| standards | EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14 | |
| product certifications | NEMA UL 508 | |
| vibration resistance | 7 gn (f = 2500 Hz) conforming to IEC 60068-2-6 | |
| shock resistance | 50 gn conforming to IEC 60068-2-27 | |

Offer Sustainability

| 785901750277 | 785901750277 |
|--|--|
| Compliant - since 0921 - Schneider Electric declaration of conformity | Compliant - since 0921 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

| Warranty period | | | |
|-----------------|--|--|--|
| | | | |

18 months