


LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
		NC	NEW RELEASE PER E.O. P20485	06AUG2010	IG RDR
		A	REVISED PER E.O. P20776	04FEB2011	IG RDR
		B	REVISED PER ECO-15-005416	22JUL2015	JA DM
		B1	REVISED PER ECO-16-012884	31AUG2016	JA DM



- 5. 3 SIZE 4: 4 AWG [21.0-25.0 mm<sup>2</sup>] AND 4 SIZE 16.
- 4 NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.
- 3 MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)  
RETAINING RING: PA66 GF10 (GREEN)  
GROMMET: SILICONE (ORANGE-RED)

2 SEE 0425-021-0000 APPLICATION SPECIFICATION  
 A. RECOMMENDED WIRE INSULATION RANGE  
 B. CONTACT REMOVAL TOOL

1. THIS PLUG MATES WITH HDP24-24-7PX-XXXX RECEPTACLE  
 X = SEAL TYPE (N,T,E)  
 XXXX = MODIFICATION

NOTES:

TE INTERNAL PN	DEUTSCH PN
HDP26-24-7SN-C038	HDP26-24-7SN-C038

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 01APR2010 ILINA GRANICHAROVA		TE Connectivity	
DIMENSIONS: INCHES [mm]		CHK 05AUG2010 BRICE BYFORD			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 05AUG2010 STEVE BEARD		NAME PLUG CONNECTOR SHELL SIZE 24, -C038 MOD HDP SERIES	
0 PLC ±		PRODUCT SPEC 0425-021-0000		SIZE A3	
1 PLC ±		APPLICATION SPEC 2		CAGE CODE 4AFU8	
2 PLC ±		WEIGHT 52.08g		DRAWING NO HDP26-24-7SN-C038	
3 PLC ±.015 [0.38]		Customer Drawing		RESTRICTED TO -	
4 PLC ±		SCALE 2:1		SHEET 1 OF 1	
4 ANGLES ±0°30'0"		REV B1			
MATERIAL 3					
FINISH					