


# PIN RECEPTACLES

**FOR .015" - .020" DIAMETER PINS (#11 CONTACT)  
AND .015" - .022" DIAMETER PINS (#21 CONTACT)  
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

## 8467

**8467-0-15-XX-21-XX-04-0**


Hex press-fit in .036 plated through-hole



## 6192

**6192-0-15-XX-21-XX-04-0**


Square press-fit in .032 plated through-hole



## 9553

**9553-0-15-XX-X1-XX-04-0**


Hex press-fit in .041 plated through-hole



## 5531

**5531-0-15-XX-21-XX-10-0**


Hex press-fit in .041 plated through-hole



## 7553

**7553-0-15-XX-11-XX-10-0**


Hex press-fit in .041 plated through-hole



## 9407

**9407-0-15-XX-11-XX-10-0**


Solder mount in .040 min. mounting hole



## 9462

**9462-0-15-XX-21-XX-04-0**


Hex press-fit in .043 plated through-hole



## 1147

**1147-0-18-XX-21-XX-10-0**


Press-fit in .043 min. mounting hole  
Accepts wire sizes up to .014" dia.



## 3061

**3061-0-19-XX-21-XX-10-0**


Wire Crimp Termination. Accepts wire sizes 28 AWG Max. / 32 AWG Min.



## 0579

**0579-0-15-XX-X1-XX-10-0**


Press-fit in .040 mounting hole



## 8874

**8874-0-15-XX-11-XX-10-0**


Bottom entry surface mount  
See page 152 for application details



## 0613

**0613-0-15-XX-21-XX-10-0**

Press-fit in .047 mounting hole



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$

Diameters:  $\pm .002$

Angles:  $\pm 2^\circ$



**ORDER CODE: XXXX - X - 1X - XX - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

**01** 200  $\mu$ " TIN/LEAD OVER NICKEL

◆ **80** 200  $\mu$ " TIN OVER NICKEL (RoHS)

◆ **15** 10  $\mu$ " GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

**02** 100  $\mu$ " TIN/LEAD OVER NICKEL

◆ **84** 100  $\mu$ " TIN OVER NICKEL (RoHS)

◆ **27** 30  $\mu$ " GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#11 or #21 CONTACT (DATA ON PAGE 251)**

(For alternate contact choices, see group A on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com