

NOTES:

I. MATERIALS AND FINISHES:
HD-BNC STR PLUG - BRASS, NICKEL PLATING
BERYLLIUM COPPER, NICKEL PLATING
PHOSPHOR BRONZE, GOLD PLATING
PTFE, NATURAL
BNC CRIMP JACK - BRASS, NICKEL PLATING
PHOSPHOR BRONZE, GOLD PLATING
PTFE, NATURAL
CABLE - BELDEN 4855R

2. ELECTRICAL:
A. IMPEDANCE: 75 OHM
3. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-850-193-XXX, AND DATE CODE"

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	10-Apr-18	7641	BMG

SCALE 0.500

LENGTH "L" (SEE TABLE)

INTERFACE SERIES: HD-BNC PLUG

HEAT SHRINK TUBE TYP(2)

LENGTH TABLE		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]
95-850-193-006	-	6.00 [0.152]
	95-850-193M025	9.84 [0.250]
95-850-193-012	-	12.00 [0.305]
95-850-193-018	-	18.00 [0.457]
-	95-850-193M050	19.69 [0.500]
95-850-193-024	-	24.00 [0.610]
-	95-850-193M075	29.53 [0.750]
95-850-193-036	-	36.00 [0.914]
-	95-850-193M100	39.37 [1.000]
95-850-193-048	-	48.00 [1.219]
-	95-850-193M125	49.21 [1.250]
-	95-850-193M150	59.06 [1.500]
95-850-193-060	-	60.00 [1.524]
95-850-193-072	-	72.00 [1.829]
-	95-850-193M200	78.74 [2.000]
-	95-850-193M300	118.11 [3.000]
95-850-193-120	-	120.00 [3.048]
95-850-193-144	-	144.00 [3.658]
95-850-193-180	-	180.00 [4.572]
	95-850-193M500	196.85 [5.000]
95-850-193-300	-	300.00 [7.620]
-	95-850-193M10L	393.70 [10.000]
95-850-193-600	-	600.00 [15.240]
-	95-850-193M20L	787.40 [20.000]
95-850-193-900	-	900.00 [22.860]
-	95-850-193M30L	1181.10 [30.000]
95-850-193L100	-	1200.00 [30.480]

DESIGN REQUIREMENTS:

☒ FREQUENCY : DC TO 12 GHz

☐ VSWR : 1 MAX

☐ INS. LOSS : dB MAX

☐ CONTINUITY

☒ HI-POT: 1000 VRMS

☐ OTHER

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0.381 mm) ±.005 (0.127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

SEE NOTES

REFERENCE
EAR # 7771

CONFIGURATION LEVEL: In Work

FINISH

DRAWN
B. GREENBAUM

ENGINEER
B. GREENBAUM

APPROVED
K. CAPOZZI

CAD FILE

DATE
23-Jun-17

DATE
23-Jun-17

DATE
10-Apr-18

TITLE
BNC STR CRIMP JACK TO
HD-BNC STR CRIMP PLUG
ON BELDEN 4855R,
VARIOUS LENGTHS

SCALE: 1.7:1.0

SHEET 2 OF 2

DWG SIZE
B

REV
A

Amphenol RF
www.amphenolrf.com

DRAWING NO. 95-850-193-XXX

ITEM NO. 95-850-193-XXX

PART NO. 95-850-193-XXX

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY