

MODEL TL-5101


International size reference: 1/2AA, ER14252

TECHNICAL DATA

(Typical values @+25°C for batteries stored for one year or less)



■ Nominal capacity @ 0.5 mA, to 2V	0.95 Ah
■ Rated voltage	3.6 V
■ Weight	9.2g (0.324 oz)
■ Volume	4.3 cc
■ Operating temperature range	-55°C to +85°C
■ U.L. Component Recognition, MH 12193	

TADIRAN
LITHIUM
BATTERIES



AVAILABLE TERMINATIONS

SUFFIX- /S STANDARD	15-5101-21000
SUFFIX- /T SOLDER TABS	15-5101-31000
SUFFIX- /P AXIAL PINS	15-5101-41000
SUFFIX- /PT2 RADIAL PINS	15-5101-36000
SUFFIX- /TP POLARIZED TABS	15-5101-52000
SUFFIX- /PT POLARIZED TABS	15-5101-53000



MEMORY BACKUP

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. B 03/03

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tadiran Batteries:](#)

[TL-5101/PBP](#) [TL-5101/SBP](#)