

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

5035663902

Status:


Active

Overview:

FFC-FPC (SMT)

Description:

Easy-On FPC Connector, 0.30mm Pitch, Right-Angle, Bottom Contact, 0.95mm Height, 39 Circuits, Gold over Nickel Plating



Documents:	
3D Model	Application Specification 5035660000-A00 (PDF)
Drawing (PDF)	Packaging Specification 5035669200-200 (PDF)
3D Model (PDF)	RoHS Certificate of Compliance (PDF)
Product Specification 5035660000-000 (PDF)	

General	
Product Family	FFC/FPC Connectors
Series	503566
Overview	FFC-FPC (SMT)
Product Name	Easy-On
UPC	191128129879
Physical	
Actuator Type	Flip
Circuits (Loaded)	39
Circuits (maximum)	39
Color - Resin	Natural
Contact Position	Bottom
Durability (mating cycles max)	10
Mated Height	0.95mm
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	Liquid Crystal Polymer
Net Weight	56.126/mg
Number of Rows	1
Orientation	Right Angle
PCB Locator	No
PCB Mounting	Surface Mount
PCB Retention	None
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	0.30mm
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-40° to +105°C
Wire/Cable Type	FPC only
Electrical	
Current - Maximum per Contact	0.3A
Voltage - Maximum	50V
Material Info	
Reference - Drawing Numbers	
Application Specification	5035660000-A00
Packaging Specification	5035669200-200
Product Specification	5035660000-000
Sales Drawing	5035660001-000, 5035661001-000

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - ECHA_01_2020 (16 January 2020	
Halogen-Free	
Status	
Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

503566 Series

This document was generated on 03/16/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION