

## Coaxial Cable Connector 16\_N-50-7-28/133\_N

### Description

Right angle cable plug

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 11 GHz      |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | crimped   |
| Outer contact  | crimped   |
| Weight         | 0.0642 kg |

#### Environmental Data

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU, RoHS      | compliant        |

#### Material Data

| Piece Parts    | Material              | Surface Plating                   |
|----------------|-----------------------|-----------------------------------|
| Centre contact | Bronze / Brass        | Gold Plating (Nickel underplated) |
| Outer contact  | Brass                 | SUCOPLATE (R) Plating             |
| Body           | Brass                 | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE            |                                   |
| Coupling nut   | Brass                 | SUCOPLATE (R) Plating             |
| Gasket         | VMQ (Silicone rubber) |                                   |
| Crimp ferrule  | Brass                 | SUCOPLATE (R) Plating             |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00005773   |
| Catalogue drawing    | DOU-00008036   |
| Assembly instruction | DOC-0000178649 |

### Ordering Information

|                |                     |
|----------------|---------------------|
| Single package | 16_N-50-7-28/133_NE |
|----------------|---------------------|

### Additional Information

|                 |                                      |
|-----------------|--------------------------------------|
| Suitable cables | RG_393_/U, ENVIROFLEX_393, RG_225_/U |
|-----------------|--------------------------------------|