ZRB18AR61A226ME01# "#" indicates a package specification code.
















< List of part numbers with package codes > ZRB18AR61A226ME01L , ZRB18AR61A226ME01K

Shape



	L size	1.6 ±0.2mm
	W size	0.8 ±0.2mm
	Tsize	1.0 ±0.2mm
	External terminal width e	0.2 to 0.65mm
	Distance between external terminals g	0.6mm min.
	Size code in inch(mm)	0603 (1608M)

Notes

Derating1



Packaging	Specifications	Minimum quantity
L	φ180mm Embossed taping	3000
K	φ330mm Embossed taping	8000

Mass (typ.)	
1 piece	9.9mg
φ180mm Reel	79g

Specifications

Capacitance	22μF ±20%
Rated voltage	10Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 85℃
Operating temperature range	-55 to 85℃

1 of 1



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.