

4

3

2

1

NUMBER

C-172076

三角接 (3rd ANGLE PROJECTION)

9.0

"A"

"A"

27.8

7.2

8.3

5

ヒケ又は不貫通穴
SHRINK MARK AND/OR UNTHROUGH HOLE.

断面 "A"-"A"
(SECT "A"-"A")

10

-AMP

NOTES,

1. PRODUCT SPECIFICATION 108-5127

2. APPLICABLE CONTACT
P/N ; 170327,170328,170329

3. SEE CP78-26023. ABOUT APPLICABLE TAB.

4 MATERIAL ; 6/6 NYLON (94V-0)

5 THERE ARE A FEW CASES THAT SHRINK MARK AND/OR UNTHROUGH HOLE OCCURS IN THIS AREA, BUT NOT INFLUENCE TO CONN,FUNCTION.

6 COMPLY WITH GLOW WIRE REQUIREMENT FOR PARTS OF NON-METALLIC MATERIAL SUPPORTING A CURRENT CARRYING CONNECTION DETAILED IN IEC 60335-1, SECTION 30 (GWT), (GWT, UL94V-0)

OBSOLETE

7-172076-1	NATURAL	△
2-172076-7	(RED) 赤	△
2-172076-6	(BLUE) 青	△
2-172076-5	(GREEN) 緑	△
2-172076-4	(YELLOW) 黄	△
2-172076-2	(BLACK) 黒	△
2-172076-1	(NATURAL) 自然色	△
172076-7	(RED) 赤	
172076-6	(BLUE) 青	
172076-5	(GREEN) 緑	
172076-4	(YELLOW) 黄	
172076-2	(BLACK) 黒	
172076-1	(NATURAL) 自然色	
型番 (P/N)	色 (COLOR)	注 (NOTE)

PRINT DIST

単位: mm DIMENSIONS IN MM. DO NOT SCALE PRINT

TE Connectivity

250 シリーズ 1極 ポジティブロック (マークII)ハウジング
250 SERIES 1 Pos POSITIVE LOCK (MK-II) HOUSING

一般公差 (GENERAL TOLERANCE)

10以下: ±0.2
10を超え 30以下: ±0.25
30を超え 100以下: ±0.3
角 度: ±3°

尺 度 (SCALE)
4-1

REV.
H3

SHEET
1 OF 1

DR. 17. JAN. '95 DE. 17. JAN. '95
M. SUZUKI M. SUZUKI

CHK. 20. JAN. '95 APP. 20. JAN. '95
H. TAGUTCH H. TAGUTCH

H3

REVISED PER ECR-16-007334

24MAY2016

NK

LP

REV

DESCRIPTION

DATE

DWN

APVD