








Stecklänge / mating length




E = early mate, late break / voreilend
S = standard
L = late mate, early break / nacheilend



Bestückungsplan / contact layout



Leiterplatten-Lochbild / PCB drillhole pattern



Gerader Anschluss 0,6x0,6mm / straight terminal 0,6x0,6mm
Isolierwerkstoff / housing material : PBT GF 30

Bauart 4 / type 4

Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Maße und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Bedruckung siehe Zeichnung 294905

Marking see drawing 294905

Information:				Tolerances				Scale		2:1	
						All Dimensions in mm					
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation Messerleiste RD 128 <i>Male Connector RD 128</i>			
								www.ERNI.com		374463	
-		02.06.2009						I			
Index		Date						Class		STVRD	
										A3	

Copyright by ERNI GmbH
Property notice pursuant to ISO 10116 to be observed.

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[374463](#)