




N=Number of contacts
Dimension A&B

DIM A	$N \times 10 + 3.5$
DIM B	$(N-1) \times 10$

Poles \ Tol.	Dim A&B
4p	± 0.20
5-10p	± 0.30
11-24p	± 0.40
25-30p	± 0.50

SIGN	DATE	DESCRIPTION	APPROVER
	3/30/09	Structure changed	JODY
	3/30/09	Temperature changed from -40° 105°C to -40° 115°C	JODY
	11/13/12	Change the screw plating specification	Jacky
	11/13/12	Change the dimensional tolerance	Jacky
	11/13/12	Add the dimensional label	Jacky
<i>THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</i>			

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	300 V, 20 A
WITHSTAND VOLTAGE:	AC 2000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
OPERATING TEMPERATURE RANG:	Δ -40 °C ~+115 °C
SCREW TORQUE VALUE:	12Lb-In.
WIRE RANGE:	22 - 12 AWG
1) MOLDED PARTS:	THERMOPLASTIC , UL 94 V-0 BLACK
2) TERMINAL:	BRASS, 0.8t, Tin PLATED
3) TERMINAL SCREWS:	STEEL, M3.5

APPROVAL: us

Critical dimension: ∇_C

PART NO.:

YK 601 xx 0 x x 00G

— G:RoHS compliant(lead<4%)
in copper alloy

NO. OF POLES

04: 4 POLES

05: 5 POLES

06: 6 POLES

•

•

•

30: 30 POLES

— MARK

0: "@" MARK

1: "ANY" MARK

— TERMINAL & SCREW PLATED

0: TERMINAL & SCREW: G/F

△ 1: TERMINAL: G/F, SCREW: Zinc

2: TERMINAL: S_n, SCREW: G/F

ANYTEK				CUSTOMER COPY			
				ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE		YK-601 Without Flange& Cover Series(4-30P)					
PART NO.		YK601xx0xx00G		DWG NO.	8YK0002-601		
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Jacky 2012.11.13	Jacky 2012.11.13			X. ±0.50
							UNIT: mm
					SCALE: NONE		X.XX ±0.10
					SHEET: 01/01		X° ±1°
					REV: D		