

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company



**NO O-RING
REQUIRED!**

Heyco® -Tite Liquid Tight Cordgrips

Multi-Hole with Integral Sealing Ring

Sequenced by Conductor Size

The Ultimate in Liquid Tight Strain Relief Protection

- Heyco® **Multi-hole glands** provide the widest range of conductor through-hole size and number configurations, many of which are agency approved. See the tabular charts for specific approvals for specific parts. These approvals are not “global” or implied approvals; they are both real and part specific.
- Integral Sealing Ring ensures a superior seal at the clearance or threaded mounting hole location, every time.
- IP 68 rated.
- Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- For body part dimensions see page 3-1, 3-3, and 3-4.
- Multi-hole glands are only to be used with Heyco Liquid Tight Cordgrips and are not sold separately.
- Consult Heyco for Cordgrips molded in other colors.

| CONDUCTORS | | NPT HUB* | | PG HUB** | | METRIC HUB** | | |
|---|-----|----------------------|---------------------|----------------|------------|----------------|----------|----------|
| Hole Size mm. | No. | UL or IEC Part No. | Black Desc. | Black Part No. | Desc. | Black Part No. | Desc. | |
| Round, Open Holes – consult Heyco for Snap-in-2 Hub versions | | | | | | | | |
| 1,4 | 4 | | M3228GAP LTCG 3/8 | M3210GAP | LTCG 9 | M4336GAP | LTCG M16 | |
| | 6 | | M3228GAZ LTCG 3/8 | M3210GAZ | LTCG 9 | M4336GAZ | LTCG M16 | |
| | 10 | | M3228GE LTCG 3/8 | M3210GE | LTCG 9 | M4336GE | LTCG M16 | |
| 1,5 | 2 | | M4516GGBA LTCG 1/4 | M3207GGBA | LTCG 7 | M4332GGBA | LTCG M12 | |
| | 3 | | – | M3213GF | LTCG 11 | – | – | |
| 1,6 | 5 | | M3228GG LTCG 3/8 | M3210GG | LTCG 9 | M4336GG | LTCG M16 | |
| 1,7 | 2 | | M3228GH LTCG 3/8 | M3210GH | LTCG 9 | M4336GH | LTCG M16 | |
| | 3 | | M3228GJ LTCG 3/8 | M3210GJ | LTCG 9 | M4336GJ | LTCG M16 | |
| | 4 | | M3228GK LTCG 3/8 | M3210GK | LTCG 9 | M4336GK | LTCG M16 | |
| 2,0 | 3 | | M3231GL LTCG 1/2 | M3216GL | LTCG 13 | M4340GL | LTCG M20 | |
| 2,3 | 4 | | M3228GM LTCG 3/8 | M3210GM | LTCG 9 | M4336GM | LTCG M16 | |
| 2,5 | 2 | | M3231GN LTCG 1/2 | M3216GN | LTCG 13 | M4340GN | LTCG M20 | |
| 2,8 | 4 | | – | M3213GAY | LTCG 11 | – | – | |
| 3,0 | 2 | | M3228GP LTCG 3/8 | M3210GP | LTCG 9 | M4336GP | LTCG M16 | |
| | | | – | M3213GB | LTCG 11*** | – | – | |
| | | | – | M3213GP | LTCG 11 | – | – | |
| | 3 | | – | – | M3213GQ | LTCG 11 | – | – |
| | | | M3231GQ | LTCG 1/2 | M3216GQ | LTCG 13 | M4340GQ | LTCG M20 |
| | | | M3200GQ | LTCG LL 1/2 | M3219GQ | LTCG 16 | – | – |
| | | | M3200GR | LTCG LL 1/2 | M3219GR | LTCG 16 | – | – |
| 6 | | M3231GS | LTCG 1/2 | M3216GS | LTCG 13 | M4340GS | LTCG M20 | |
| | | M3200GS | LTCG LL 1/2 | M3219GS | LTCG 16 | – | – | |
| 3,8 | 2 | | M3231GT LTCG 1/2 | M3216GT | LTCG 13 | M4340GT | LTCG M20 | |
| | 6 | | M3200GW LTCG LL 1/2 | M3219GW | LTCG 16 | – | – | |
| 4,0 | 2 | | – | M3213GAK | LTCG 11 | – | – | |
| | 3 | | M3231GX LTCG 1/2 | M3216GX | LTCG 13 | M4340GX | LTCG M20 | |
| | | | M3200GX | LTCG LL 1/2 | M3219GX | LTCG 16 | – | – |
| | 4 | | M3200GY LTCG LL 1/2 | M3219GY | LTCG 16 | – | – | |
| | 5 | | M3200GZ LTCG LL 1/2 | M3219GZ | LTCG 16 | – | – | |
| 6 | | M3200GGB LTCG LL 1/2 | M3219GGB | LTCG 16 | – | – | | |

Standard color black.

*Locknuts not included. For Locknut specifications or to order Locknuts separately, see pages 3-47 & 3-48.

**Unassembled Nylon Locknuts INCLUDED.

***Short Thread



Multi-hole Gland (typical)

Quick Specs

| | |
|---------------------|--|
| Material | Nylon 6/6 with TPE Sealing Gland |
| Flammability Rating | 94V-2 Standard |
| Temperature Range | Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C) |
| IP Rating | IP 68 |