

## ZFK3DSA 1,5-5,08-16 BUBDWHM-24 - 1705891

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, nominal current: 12 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 16, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: blue

The figure shows an 10-position version

#### Your advantages

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☐ Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- Conductor connection on several levels enables higher contact density
- The latching on the side enables various numbers of positions to be combined

















#### **Key Commercial Data**

Packing unit	10 pc
GTIN	4 046356 806190
GTIN	4046356806190

#### Technical data

## Item properties

Brief article description	PCB terminal block
Range of articles	ZFK3DS(A) 1,5
Pitch	5.08 mm
Number of positions	16
Connection method	Spring-cage connection
Mounting type	Wave soldering
Pin layout	Linear pinning
Number of levels	3

#### Electrical parameters

Rated current	12 A
Rated insulation voltage (III/2)	400 V



# ZFK3DSA 1,5-5,08-16 BUBDWHM-24 - 1705891

## Technical data

## Electrical parameters

Rated surge voltage (III/2)	4 kV
-----------------------------	------

## Connection capacity

Conductor cross section solid	0.2 mm² 2.5 mm²
Conductor cross section flexible	0.2 mm² 1.5 mm²
Conductor cross section AWG / kcmil	24 14
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 1.5 mm²
Stripping length	7.5 mm

#### Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	hot-dip tin-plated
Metal surface terminal point (top layer)	Tin (10 - 16 μm Sn)
Metal surface soldering area (top layer)	Tin (10 - 16 μm Sn)

## Material data - housing

Insulating material	PA
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775
Temperature for the ball pressure test according to EN 60695-10-2	125 °C

## Dimensions for the product

Length [1]	32.2 mm
Pitch	5.08 mm
Height (without solder pin)	37 mm
Solder pin [P]	3.4 mm
Pin dimensions	0.7 x 1 mm
Dimension a	76.2 mm

## Dimensions for PCB design

Hole diameter	1.3 mm

## Packaging information

Type of packaging	packed in cardboard
Pieces per package	10
Denomination packing units	Pcs.

#### Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C



# ZFK3DSA 1,5-5,08-16 BUBDWHM-24 - 1705891

## Technical data

۸m	hiant	conditions

Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C

#### Electrical tests

Rated current	12 A
Rated insulation voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV

## Air clearances and creepage distances

Insulating material group	1
Voltage	250 V
Rated insulation voltage (III/3)	250 V
Rated insulation voltage (III/2)	400 V
Rated insulation voltage (II/2)	630 V
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV

#### Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

Approvals

Approvals

EAC

Ex Approvals

## Approval details

EAC []



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com