



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. CONTACT RATING: 3 AMPS @ 125-VL, CSA
  4. ELECTRICAL LIFE: 100,000 CYCLES TYP.
  5. MECHANICAL LIFE: 1,000,000 CYCLES TYP.
  6. DIELECTRIC STRENGTH 1,000 V RMS @ SEA LEVEL
  7. OPERATING TEMPERATURE: -25°C TO 85°C
  8. OPERATING FORCE 125 GF ±40
  9. ▲ DENOTES CRITICAL PARAMETER.

*O.P. (mm)	*P.T. (mm)
5.5 ± 0.2	1.8 MAX.

\*O.P. = Operating Point  
\*P.T. = Pre-Travel

**E-SWITCH®**

B	20204	UPDATE P.T.	10/11/11	BMA
A	13911	RELEASED FOR PRODUCTION	4/14/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
DM0850300F125P1A		4:1	4/14/04	AR	P030010	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED