

## Printed-circuit board connector - PT 1,5/ 3-PH-3,5-A BD:10-12 - 1702520

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB connector, nominal current: 8 A, number of positions: 3, pitch: 3.5 mm, connection method: Screw connection with wire protector, color: green, contact surface: Tin



The figure shows a 10-position version of the product

### Your advantages

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ High terminal block capacity thanks to rectangular terminal block space
- ✓ Allows connection of two conductors
- ✓ The latching on the side enables various numbers of positions to be combined



### Key Commercial Data

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Packing unit | 250 pc                                                                               |
| GTIN         |  |
| GTIN         | 4046356589345                                                                        |

### Technical data

#### Dimensions

|             |        |
|-------------|--------|
| Pitch       | 3.5 mm |
| Dimension a | 7 mm   |

#### General

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Range of articles                | PT 1,5/...-PH                        |
| Number of positions              | 3                                    |
| Connection method                | Screw connection with wire protector |
| Rated voltage (III/3)            | 160 V                                |
| Connection in acc. with standard | EN-VDE                               |
| Nominal current $I_N$            | 8 A                                  |
| Nominal cross section            | 1.5 mm²                              |

# Printed-circuit board connector - PT 1,5/ 3-PH-3,5-A BD:10-12 - 1702520

## Technical data

### Connection data

|                                                                         |                      |
|-------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                   | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                   | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max. | 0.75 mm <sup>2</sup> |
| Conductor cross section AWG min.                                        | 26                   |
| Conductor cross section AWG max.                                        | 16                   |
| 2 conductors with same cross section, solid min.                        | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                        | 0.34 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded min.                     | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded max.                     | 0.5 mm <sup>2</sup>  |

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CUL    |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

Approvals

EAC / cULus Recognized

Ex Approvals

### Approval details

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|---------|

## Printed-circuit board connector - PT 1,5/ 3-PH-3,5-A BD:10-12 - 1702520

### Approvals

|                                                                                                                                                                                                                                                                          |       |       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| cULus Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E60425-20030211 |       |       |
|                                                                                                                                                                                                                                                                          | D     | B     |
| Nominal voltage UN                                                                                                                                                                                                                                                       | 300 V | 300 V |
| Nominal current IN                                                                                                                                                                                                                                                       | 10 A  | 10 A  |
| mm²/AWG/kcmil                                                                                                                                                                                                                                                            | 26-16 | 26-16 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>