






SMA FEMALE - SMP-L MALE ADAPTOR
R191.593.400
LIMITED-DETENT

Série : ADAPT


 *2.7 min
for locking

PANEL CUT OUT


	mm	
	Maxi	mini
A	4.95	4.85
B	M2.5	
C	12.25	12.15



All dimensions are in mm.

COMPONENTS	MATERIALS	PLATING (μm)
BODY	BRASS	NPGR
CENTER CONTACT	BERYLLIUM COPPER	GOLD 1.27 OVER NICKEL 1.27
OUTER CONTACT	-	-
INSULATOR	PTFE	-
GASKET	-	-
OTHERS PARTS	-	-
-	-	-
-	-	-

Issue : 1223 A

In the effort to improve our products, we reserve the rights to make changes judged to be necessary.

RADIAL

SMA FEMALE - SMP-L MALE ADAPTOR**R191.593.400****LIMITED-DETENT**

Série : ADAPT

PACKAGING

Standard	Unit	Other
1	-	Contact us

SPECIFICATION**ELECTRICAL CHARACTERISTICS**

Impedance	50	Ω
Frequency	0-18	GHz
VSWR	1.17 + 0,0000	x F(GHz) Maxi
Insertion loss	0.12	$\sqrt{F}(\text{GHz})$ dB Maxi
RF leakage	- (100)	- F(GHz)) dB Maxi
Voltage rating	335	Veff Maxi
Dielectric withstanding voltage	1000	Veff mini
Insulation resistance	5000	M Ω mini

ENVIRONMENTAL

Operating	-65/+165	$^{\circ}\text{C}$
Hermetic seal	NA	Atm.cm3/s
Panel leakage	NA	

MECHANICAL CHARACTERISTICS

Center contact retention		
Axial force – Mating end	6.7	N mini
Axial force – Opposite end	6.7	N mini
Torque	NA	N.cm mini

Recommended torque

Mating	SMA	0	N.cm
	SMP	0	N.cm
		0	N.cm
Panel nut			N.cm

Mating life	500	Cycles mini
Weight	2,7900	g

OTHER CHARACTERISTICS

Issue : 1223 A

In the effort to improve our products, we reserve the rights to make changes judged to be necessary.

