



### Main

|                                       |  |
|---------------------------------------|--|
| Range of product                      | ConneXium                                    |
| Product or component type             | Ethernet TCP/IP managed switch               |
| Concept                               | Transparent Ready                            |
| Communication port protocol           | Ethernet TCP/IP                              |
| Port Ethernet                         | 10BASE-T/100BASE-TX - 8 port(s) copper cable |
| Maximum number of switches in cascade | Unlimited                                    |

### Complementary

|                                      |   |
|--------------------------------------|---|
| Integrated connection type           | Shielded RJ45 copper cable  |
| Transmission support medium          | Twisted shielded pairs cable CAT 5E copper cable  |
| Ethernet service                     | Configuration via web server<br>Data stream control<br>FDR<br>IGMP Snooping<br>Multicast filtering<br>Priority port<br>Rapid Spanning Tree Protocol (RSTP)<br>Secure port<br>SMTP V3<br>SNTP client |
| Maximum number of switches in a ring | 50  |
| Redundancy                           | Redundant power supplies<br>Redundant single ring<br>Ring coupling  |
| Supply voltage limits                | 9.6...32 V DC SELV  |
| Power consumption in W               | 6 W   |
| Electrical connection                | Removable connector 6 ways power supply   |
| Mounting support                     | 35 mm symmetrical DIN rail  |
| Marking                              | CE  |
| Local signalling                     | 1 LED fault<br>2 LEDs P1 P2 power supplies<br>1 LED ring manager<br>1 LED stand-by<br>1 LED per channel copper port activity<br>1 LED per channel copper port status                                |
| Alarm output                         | 1 voltfree contact 1 A  |
| Alarm function                       | Power supply fault<br>Switch fault<br>Data link status  |
| Ethernet cabling system              | TF switches   |
| Width                                | 1.85 in (47 mm)   |
| Height                               | 5.16 in (131 mm)  |
| Depth                                | 4.37 in (111 mm)  |
| Product weight                       | 0.9 lb(US) (0.41 kg)  |

### Environment

|                                       |  |
|---------------------------------------|--|
| ambient air temperature for operation | 32...140 °F (0...60 °C)                      |
| relative humidity                     | > 0...95 % without condensation              |
| IP degree of protection               | IP20   |
| standards                             | EN/IEC 61131-2<br>UL 1604 Class 1 Division 2 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|   |   |
|---|---|
| Not Green Premium product   | Not Green Premium product   |
| Compliant - since 1105 - Schneider Electric declaration of conformity   | Compliant - since 1105 - Schneider Electric declaration of conformity   |
| WARNING: This product can expose you to chemicals including:  | WARNING: This product can expose you to chemicals including:  |
| Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                   | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Dimensions

