

DESIGN KIT

WE-HCC SMD High Current Cube Inductor



SIZE:

8070; 1090; 1210

TECHNICAL DATA:

L: 0.22 ~ 10 μ H
 I_R : 9.0 ~ 27 A
 I_{sat} : 8.0 ~ 60 A
 R_{dc} : 0.53 ~ 20.7 m Ω

Order Code 744 332

Version 1.0

DESIGN KIT

WE-HCC SMD High Current Cube Inductor



| | | | | | | | | | | | | | | |
|------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|---------------------------|---------------------------|
| 8070 | 744 334 003 0 | L: 0.3 μ H | 744 334 004 7 | L: 0.47 μ H | 744 334 006 8 | L: 0.68 μ H | 744 334 010 0 | L: 1.0 μ H | 744 334 015 0 | L: 1.5 μ H | 744 334 022 0 | L: 2.2 μ H | 744 334 033 0 | L: 3.3 μ H |
| | I_{R^*} : 20.5 A | I_{R^*} : 19 A | I_{R^*} : 19 A | I_{R^*} : 17 A | I_{R^*} : 16.5 A | I_{R^*} : 16.5 A | I_{R^*} : 17 A | I_{R^*} : 17 A | I_{R^*} : 16.5 A | I_{R^*} : 16.5 A | I_{R^*} : 12.5 A | I_{R^*} : 14 A | I_{R^*} : 14 A | I_{R^*} : 14 A |
| | I_{sat} : 36 A | I_{sat} : 32 A | I_{sat} : 23.5 A | I_{sat} : 24 A | I_{sat} : 18.5 A | I_{sat} : 18.5 A | I_{sat} : 12.5 A | I_{sat} : 12.5 A | I_{sat} : 12.5 A | I_{sat} : 12.5 A | I_{sat} : 8.5 A | I_{sat} : 8.5 A | I_{sat} : 8.5 A | I_{sat} : 8.5 A |
| | R_{DC} : 1.4 m Ω | R_{DC} : 1.72 m Ω | R_{DC} : 1.72 m Ω | R_{DC} : 2.95 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 4.4 m Ω | R_{DC} : 6.5 m Ω | R_{DC} : 6.5 m Ω |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| 1090 | 744 333 002 2 | L: 0.22 μ H | 744 333 003 3 | L: 0.33 μ H | 744 333 004 7 | L: 0.47 μ H | 744 333 006 8 | L: 0.68 μ H | 744 333 008 2 | L: 0.82 μ H | 744 333 010 0 | L: 1.0 μ H | 744 333 015 0 | L: 1.5 μ H |
| | I_{R^*} : 21.5 A | I_{R^*} : 21.5 A | I_{R^*} : 20.5 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 20 A | I_{R^*} : 18 A | I_{R^*} : 18 A | |
| | I_{sat} : 60 A | I_{sat} : 55 A | I_{sat} : 47 A | I_{sat} : 38 A | I_{sat} : 36 A | I_{sat} : 36 A | I_{sat} : 27.5 A | I_{sat} : 27.5 A | I_{sat} : 27.5 A | I_{sat} : 27.5 A | I_{sat} : 27 A | I_{sat} : 27 A | I_{sat} : 27 A | |
| | R_{DC} : 0.6 m Ω | R_{DC} : 0.6 m Ω | R_{DC} : 0.8 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 1.35 m Ω | R_{DC} : 2.5 m Ω | R_{DC} : 2.5 m Ω |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| 1210 | 744 332 002 2 | L: 0.22 μ H | 744 332 003 3 | L: 0.33 μ H | 744 332 004 7 | L: 0.47 μ H | 744 332 006 8 | L: 0.68 μ H | 744 332 008 2 | L: 0.82 μ H | 744 332 010 0 | L: 1.0 μ H | 744 332 015 0 | L: 1.5 μ H |
| | I_{R^*} : 27 A | I_{R^*} : 27 A | I_{R^*} : 26 A | I_{R^*} : 26 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 24 A | I_{R^*} : 19.5 A | |
| | I_{sat} : 60 A | I_{sat} : 55 A | I_{sat} : 48 A | I_{sat} : 38 A | I_{sat} : 36 A | I_{sat} : 36 A | I_{sat} : 32 A | I_{sat} : 32 A | I_{sat} : 32 A | I_{sat} : 32 A | I_{sat} : 32 A | I_{sat} : 27 A | I_{sat} : 27 A | |
| | R_{DC} : 0.53 m Ω | R_{DC} : 0.53 m Ω | R_{DC} : 0.72 m Ω | R_{DC} : 0.72 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 1.17 m Ω | R_{DC} : 2.1 m Ω | R_{DC} : 2.1 m Ω |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

EMC COMPONENTS | INDUCTORS | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | POWER ELEMENTS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2011