

# Protective hose - WP-SPIRAL PU C HF 14 - 3240857

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective hose, spring steel wire with PU coating, highly stranded

The figure shows a version of the article

## Key Commercial Data

Packing unit	10 M
Minimum order quantity	10 M
GTIN	 4 046356 736831
Weight per Piece (excluding packing)	99.99 g
Weight per piece (including packing)	99.99 g
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

### Dimensions

Inner diameter (f)	10.00 mm
Outside diameter	14.00 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Short-term temperature	120 °C

### General

Color	blue
Type	Spring steel wire with PU coating
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V2
Material	PU
Bending radius, static	10.00 mm

### Standards and Regulations

Resistance to UV radiation	no
----------------------------	----

# Protective hose - WP-SPIRAL PU C HF 14 - 3240857

## Technical data

### Standards and Regulations

Halogen-free	yes
Flammability rating according to UL 94	V2

## Classifications

### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27430304

### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001177
ETIM 5.0	EC001177

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

Approvals

VDE Zeichengenehmigung

---

Ex Approvals

---


Approvals submitted

---

Approval details

## Protective hose - WP-SPIRAL PU C HF 14 - 3240857

### Approvals

VDE Zeichengenehmigung 

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>