




SPECIFICATIONS:

Material Properties:

- Dissipative Polyvinylchloride (PVC)
- Material Thickness: 0.012" (1S) front & back
- Material Tolerance (thickness): +/-10%
- Material Finish: Matte
- 1" header imprinted with ESD Protective Symbol
- 2-1/2" x 3-1/2" Badge Holder display
- 3-1/2" x 5-13/16" OD

Electrical Properties:

- Rs: 1×10^6 to $< 1 \times 10^{11}$ ohms per ANSI/ESD STM11.11

Item	Description
07474	ESD Pocket Protector

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20 section 2.4 Sources of Static Electricity]



Specifications and procedures are subject to change without notice

Made in the
United States of America

ESD POCKET PROTECTOR

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEBSITE: Desco.com
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING
NUMBER**

07474

DATE
February
2014

Dimensional tolerances are +/- 1/16" unless specified