

Cable gland - G-INS-M32-M68N-PNES-GY - 1411127

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide 6, External cable diameter 15 mm ... 21 mm, Shielding: No, Connecting thread: M32, Color: silver grey

The illustration shows version G-INS-M25-M68N-PNES-GY

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	28.0 GRM
Custom tariff number	39269097
Country of origin	Turkey

Technical data

Dimensions

Length	50.8 mm
Length without connecting thread	40.8 mm
Connecting thread diameter	32 mm
Wrench size, union nut	36 mm
Wrench size, support	36 mm
Hexagon angular dimension GRP	40.9 mm
Length of the connecting thread	10 mm
External cable diameter	15 mm ... 21 mm

Ambient conditions

Degree of protection	IP68
	IP68 (5 bar, 30 min.)

Cable gland - G-INS-M32-M68N-PNES-GY - 1411127

Technical data

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C (for a short period up to 150 °C)
---------------------------------	--

General

Cable gland material	Polyamide 6
Seal material	Neoprene
Cable seal material	Neoprene
Shielded	No
Thread type on connection side	M32
Torque	3 Nm ... 4 Nm (Union nut)
Inflammability class according to UL 94	V2
Color	silver gray
	silver grey

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

CSA / UL Recognized / VDE Zeichengenehmigung

Ex Approvals


Approvals submitted


Approval details

Cable gland - G-INS-M32-M68N-PNES-GY - 1411127

Approvals



UL Recognized 

VDE Zeichengenehmigung 

Drawings

Dimensional drawing

