



### Main

|                           |                                  |
|---------------------------|----------------------------------|
| Range of product          | Harmony 9001K<br>Harmony 9001SK  |
| Product or component type | Empty enclosure                  |
| Device short name         | 9001K                            |
| Number of cut-out         | 3 cut-outs                       |
| Cable entry               | 1 entry tapped for 3/4" knockout |

### Complementary

|                     |                                          |
|---------------------|------------------------------------------|
| Product destination | For Ø 30 mm control and signalling units |
| Material            | Stainless steel                          |
| Product weight      | 3.78 lb(US) (1.715 kg)                   |

### Environment

|                                       |                                                  |
|---------------------------------------|--------------------------------------------------|
| protective treatment                  | TH                                               |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                       |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                       |
| overvoltage category                  | II conforming to IEC 61140                       |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 3<br>NEMA 4<br>NEMA 4X |

### Offer Sustainability


|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                      | Green Premium product                                                                                                      |
| Compliant - since 1002 - Schneider Electric declaration of conformity                                                      | Compliant - since 1002 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Nickel compounds, which is known to the State of California to cause cancer, and                                           | Nickel compounds, which is known to the State of California to cause cancer, and                                           |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

### Dimensions

Below drawing shows a 3-hole enclosure. Refer to the product characteristics to get the number of holes



| a   |       | G   |      |
|-----|-------|-----|------|
| mm  | in.   | mm  | in.  |
| 260 | 10.24 | 244 | 9.61 |