



LEAD FINISH:	GOLD
CASING FINISH:	GOLD
CAPACITANCE	10pF MAX.
TEMP. RANGE	-55°C TO 125°C
CURRENT	5 AMP MAX.
WORKING VOLTAGE	125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.

SCHEMATIC



MARKING:

NONE

PACKING:

BAG: SCIF-9925-000  
 DATE CODE  
 LOT NO.  
 QTY. / BAG (200 MAX.)

USE OF HEXAVALENT CHROMIUM, MERCURY, LEAD, CADMIUM, ASBESTOS, PCT, PCB, PBB, PBDE, IS PROHIBITED IN THE MANUFACTURE OR COMPOSITION OF THIS MATERIAL AS OUTLINED IN THE INTERNATIONAL ROHS DIRECTIVE.

NOTES:

1. MAX. SOLDERING TEMP. : 245°C FOR 5 SECONDS MAX.



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [ MILLIMETERS ] DO NOT SCALE		TOLERANCES UNLESS OTHERWISE SPECIFIED		FAIRVIEW PENNSYLVANIA	
③ THIRD ANGLE PROJECTION		Dec. .x ± .x		SPECTRUM CONTROL, INC.	
CN 23355-CPD		Dec. .xx ±		Description	
CHANGE NOTICE		Dec. .xxx ±.005 [.13]		FEEDTHRU FILTER	
NO. 00		Angles ± 0° 30"		Dwn: Hassett	
		CODE IDENT. NO. 0LSP2		Date 12-30-05	
				Engt. Sinchen	
				Sheet 1 of 1	
				SCIF-9925-000	

Quality Products From The Specialists In Electro-Magnetic Compatibility