



Fig. 1

- Series 850 and 851 interconnects are available in single and double row form.
- 850 & 852 series headers use MM #4006-1 and #4006-2 pins. See page 175 details.
- 851 & 853 series sockets use MM #4890-1 and #4890-2 receptacles, that accept pin diameters from .015"-.021" See page 131 for details.
- Insulators are high temp. thermoplastic.



Fig. 2



Fig. 3



Fig. 4

Ordering Information

Fig. 1	Single Row	Right Angle Pin Header
	850-XX-0__-20-001000 Specify # of pins → 01-50	
Fig. 2	Double Row	Right Angle Pin Header
	852-XX-__-20-001000 Specify # of pins → 002-100	

For Electrical, Mechanical & Environmental Data, See pg. 4
XX=Plating Code See Below
For RoHS compliance select ◇ plating code.

SPECIFY PLATING CODE XX=	10 ◇	90	40 ◇	
Pin Plating	10μ" Au	200μ" Sn/Pb	200μ" Sn	

Fig. 3	Single Row	Right Angle Socket
	851-XX-0__-20-001000 Specify # of pins → 01-50	
Fig. 4	Double Row	Right Angle Socket
	853-XX-__-20-001000 Specify # of pins → 002-100	

For Electrical, Mechanical & Environmental Data, See pg. 4
XX=Plating Code See Below
For RoHS compliance select ◇ plating code.

SPECIFY PLATING CODE XX=		93	99	43 ◇	
Sleeve (Pin)		200μ" Sn/Pb	200μ" Sn/Pb	200μ" Sn	
Contact (Clip)		30μ" Au	200μ" Sn/Pb	30μ" Au	