



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

# LM2903, LM393/LM393A, LM293A

## Dual Differential Comparator

### Features


- Single Supply Operation: 2V to 36V
- Dual Supply Operation:  $\pm 1V$  to  $\pm 18V$
- Allow Comparison of Voltages Near Ground Potential
- Low Current Drain 800 $\mu A$  Typ.
- Compatible with all Forms of Logic
- Low Input Bias Current 25nA Typ.
- Low Input Offset Current  $\pm 5nA$  Typ.
- Low Offset Voltage  $\pm 1mV$  Typ.

### Description

The LM2903, LM393/LM393A, LM293A consist of two independent voltage comparators designed to operate from a single power supply over a wide voltage range.



### Internal Block Diagram



## Schematic Diagram



## Absolute Maximum Ratings

| Parameter   | Symbol   | Value                              | Unit |
|---|----------|------------------------------------|------|
| Power Supply Voltage                                      | VCC      | ±18 or 36                          | V    |
| Differential Input Voltage                                | VI(DIFF) | 36                                 | V    |
| Input Voltage   | VI       | -0.3 to +36                        | V    |
| Output Short Circuit to GND                               | -        | Continuous                         | -    |
| Power Dissipation, Ta = 25°C<br>8-DIP<br>8-SOIC           | PD       | 1040<br>480                        | mW   |
| Operating Temperature<br>LM393/LM393A<br>LM2903<br>LM293A | TOPR     | 0 ~ +70<br>-40 ~ +105<br>-25 ~ +85 | °C   |
| Storage Temperature                                       | TSTG     | -65 ~ +150                         | °C   |

## Thermal Data

| Parameter   | Symbol | Value      | Unit |
|---|--------|------------|------|
| Thermal Resistance Junction-Ambient Max.<br>8-DIP<br>8-SOIC | Rθja   | 120<br>260 | °C/W |

## Electrical Characteristics

( $V_{CC} = 5V$ ,  $T_A = 25^\circ C$ , unless otherwise specified)

| Parameter                       | Symbol       | Conditions   | LM293A/LM393A |                  |                | LM393 |         |                | Unit    |
|---------------------------------|--------------|--|---------------|------------------|----------------|-------|---------|----------------|---------|
|                                 |              |  | Min.          | Typ.             | Max.           | Min.  | Typ.    | Max.           |         |
| Input Offset Voltage            | $V_{IO}$     | $V_{O(P)} = 1.4V$ , $R_S = 0\Omega$  | -             | $\pm 1$          | $\pm 2$        | -     | $\pm 1$ | $\pm 5$        | mV      |
|                                 |              | $V_{CM} = 0$ to $1.5V$   Note1   | -             | -                | $\pm 4.0$      | -     | -       | $\pm 9.0$      |         |
| Input Offset Current            | $I_{IO}$     |  | -             | $\pm 5$          | $\pm 50$       | -     | $\pm 5$ | $\pm 50$       | nA      |
|                                 |              | Note1  | -             | -                | $\pm 150$      | -     | -       | $\pm 150$      |         |
| Input Bias Current              | $I_{BIAS}$   |  | -             | 65               | 250            | -     | 65      | 250            | nA      |
|                                 |              | Note1  | -             | -                | 400            | -     | -       | 400            |         |
| Input Common Mode Voltage Range | $V_{I(R)}$   |  | 0             | -                | $V_{CC} - 1.5$ | 0     | -       | $V_{CC} - 1.5$ | V       |
|                                 |              | Note1  | 0             | -                | $V_{CC} - 2$   | 0     | -       | $V_{CC} - 2$   |         |
| Supply Current                  | $I_{CC}$     | $R_L = \infty$ , $V_{CC} = 5V$   | -             | 0.6              | 1              | -     | 0.6     | 1              | mA      |
|                                 |              | $R_L = \infty$ , $V_{CC} = 30V$  | -             | 0.8              | 2.5            | -     | 0.8     | 2.5            |         |
| Voltage Gain                    | $G_V$        | $V_{CC} = 15V$ , $R_L \geq 15k\Omega$<br>(for large $V_{O(P-P)}$ swing)                    | 50            | 200              | -              | 50    | 200     | -              | V/mV    |
| Large Signal Response Time      | $T_{LRES}$   | $V_I = \text{TTL Logic Swing}$<br>$V_{REF} = 1.4V$ , $V_{RL} = 5V$ ,<br>$R_L = 5.1k\Omega$ | -             | 350              | -              | -     | 350     | -              | nS      |
| Response Time                   | $T_{RES}$    | $V_{RL} = 5V$ , $R_L = 5.1k\Omega$   | -             | 1.4              | -              | -     | 1.4     | -              | $\mu S$ |
| Output Sink Current             | $I_{SINK}$   | $V_{I(-)} \geq 1V$ , $V_{I(+)} = 0V$ ,<br>$V_{O(P)} \leq 1.5V$                             | 6             | 18               | -              | 6     | 18      | -              | mA      |
| Output Saturation Voltage       | $V_{SAT}$    | $V_{I(-)} \geq 1V$ , $V_{I(+)} = 0V$   | -             | 160              | 400            | -     | 160     | 400            | mV      |
|                                 |              | $I_{SINK} = 4mA$   Note1   | -             | -                | 700            | -     | -       | 700            |         |
| Output Leakage Current          | $I_{O(LKG)}$ | $V_{I(-)} = 0V$ ,<br>$V_{I(+)} = 1V$   |               | $V_{O(P)} = 5V$  | -              | 0.1   | -       | 0.1            | nA      |
|                                 |              |  |               | $V_{O(P)} = 30V$ | -              | -     | 1.0     | -              | 1.0     |

### Note1

LM393/LM393A:  $0 \leq T_A \leq +70^\circ C$

LM2903:  $-40 \leq T_A \leq +105^\circ C$

LM293A :  $-25 \leq T_A \leq +85^\circ C$

**Electrical Characteristics** (Continued)(V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C, unless otherwise specified)

| Parameter                       | Symbol              | Conditions   | LM2903 |      |                       | Unit |
|---------------------------------|---------------------|--|--------|------|-----------------------|------|
|                                 |                     |  | Min.   | Typ. | Max.                  |      |
| Input Offset Voltage            | V <sub>IO</sub>     | V <sub>O(P)</sub> = 1.4V, R <sub>S</sub> = 0Ω  | -      | ±1   | ±7                    | mV   |
|                                 |                     | V <sub>CM</sub> = 0 to 1.5V   Note1  | -      | ±9   | ±15                   |      |
| Input Offset Current            | I <sub>IO</sub>     |  | -      | ±5   | ±50                   | nA   |
|                                 |                     | Note1  | -      | ±50  | ±200                  |      |
| Input Bias Current              | I <sub>BIAS</sub>   |  | -      | 65   | 250                   | nA   |
|                                 |                     | Note1  | -      | -    | 500                   |      |
| Input Common Mode Voltage Range | V <sub>I(R)</sub>   |  | 0      | -    | V <sub>CC</sub> - 1.5 | V    |
|                                 |                     | Note1  | 0      | -    | V <sub>CC</sub> - 2   |      |
| Supply Current                  | I <sub>CC</sub>     | R <sub>L</sub> = ∞, V <sub>CC</sub> = 5V   | -      | 0.6  | 1                     | mA   |
|                                 |                     | R <sub>L</sub> = ∞, V <sub>CC</sub> = 30V  | -      | 1    | 2.5                   |      |
| Voltage Gain                    | GV                  | V <sub>CC</sub> = 15V, R <sub>L</sub> ≥ 15kΩ<br>(for large V <sub>O(P-P)</sub> swing)                    | 25     | 100  | -                     | V/mV |
| Large Signal Response Time      | T <sub>LR</sub>     | V <sub>I</sub> = TTL Logic Swing<br>V <sub>REF</sub> = 1.4V, V <sub>R</sub> = 5V, R <sub>L</sub> = 5.1kΩ | -      | 350  | -                     | nS   |
| Response Time                   | T <sub>R</sub>      | V <sub>R</sub> = 5V, R <sub>L</sub> = 5.1kΩ  | -      | 1.5  | -                     | μS   |
| Output Sink Current             | I <sub>SINK</sub>   | V <sub>I(-)</sub> ≥ 1V, V <sub>I(+)</sub> = 0V, V <sub>O(P)</sub> ≤ 1.5V                                 | 6      | 16   | -                     | mA   |
| Output Saturation Voltage       | V <sub>SAT</sub>    | V <sub>I(-)</sub> ≥ 1V, V <sub>I(+)</sub> = 0V   | -      | 160  | 400                   | mV   |
|                                 |                     | I <sub>SINK</sub> = 4mA   Note1  | -      | -    | 700                   |      |
| Output Leakage Current          | I <sub>O(LKG)</sub> | V <sub>I(-)</sub> = 0V, V <sub>O(P)</sub> = 5V   | -      | 0.1  | -                     | nA   |
|                                 |                     | V <sub>I(+)</sub> = 1V, V <sub>O(P)</sub> = 30V  | -      | -    | 1.0                   | μA   |

**Note1**LM393/LM393A: 0 ≤ T<sub>A</sub> ≤ +70°CLM2903: -40 ≤ T<sub>A</sub> ≤ +105°CLM293A : -25 ≤ T<sub>A</sub> ≤ +85°C

## Typical Performance Characteristics



Figure 1. Supply Current vs Supply Voltage




Figure 2. Input Current vs Supply Voltage



Figure 3. Output Saturation Voltage vs Sink Current



Figure 4. Response Time for Various Input Overdrive-Negative Transition





Figure 5. Response Time for Various Input Overdrive-Positive Transition

# Mechanical Dimensions

## Package

Dimensions in millimeters

### 8-DIP



#### NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MS-001, VARIATIONS BA
- B. CONTROLLING DIMENSIONS ARE IN INCHES  
REFERENCE DIMENSIONS ARE IN MILLIMETERS
- C. DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS.  
MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED .010 INCHES OR 0.25MM.
- D. DOES NOT INCLUDE DAMBAR PROTRUSIONS.  
DAMBAR PROTRUSIONS SHALL NOT EXCEED .010 INCHES OR 0.25MM.
- E. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.






N08EREVG

# Mechanical Dimensions (Continued)

## Package

Dimensions in millimeters

### 8-SOIC



NOTES: UNLESS OTHERWISE SPECIFIED

- A) THIS PACKAGE CONFORMS TO JEDEC MS-012, VARIATION AA, ISSUE C,
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
- D) LANDPATTERN STANDARD: SOIC127P600X175-8M.
- E) DRAWING FILENAME: M08AREV13



## Ordering Information

| Product Number | Operating Temperature | Package | Packing Method |
|----------------|-----------------------|---------|----------------|
| LM393N         | 0 ~ +70°C             | 8-DIP   | Rail           |
| LM393AN        |                       |         | Rail           |
| LM393M         |                       | 8-SOIC  | Rail           |
| LM393MX        |                       |         | Tape & Reel    |
| LM393AM        |                       |         | Rail           |
| LM393AMX       |                       |         | Tape & Reel    |
| LM2903N        | -40 ~ +105°C          | 8-DIP   | Rail           |
| LM2903M        |                       | 8-SOIC  | Rail           |
| LM2903MX       |                       |         | Tape & Reel    |
| LM293AN        | -25 ~ +85°C           | 8-DIP   | Rail           |

### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[LM2903MX](#) [LM2903M](#) [LM2903N](#)