



9	1	TERMINAL, RING TONGUE, #10 STUD	PVC INSULATED
8	1	CONNECTOR, DUAL ROW	NYLON
7	1	LOCKNUT	STEEL/ZINC PLATED
6	1	GASKET	NEOPRENE
5	1	O-RING/SEAL	BUNA-N/COLOR:BLACK
4	5	CONTACT, SOCKET	CU ALLOY/GOLD PLATED
3	1	INSERT, 5/C	PVC/COLOR:GRAY
2	1	RCPT. SHELL, INT. THDS.	ALUMINUM/BLACK ANODIZE
1	SEE ABOVE	WIRE, 22 AWG.	PVC INSULATED
ITEM	QTY	DESCRIPTION	MATERIAL/FINISH

UL AND C(UL) RECOGNIZED
SPECIFICATIONS:
VOLTAGE RATING-250V
CURRENT RATING-4 AMPS

1. RECOMMENDED MOUNTING HOLE SIZE: .875"/.844" DIAMETER.

NOTES: UNLESS OTHERWISE SPECIFIED

QUALITY SYMBOLS	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES	SCALE ---	DWG SIZE B	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
MAJOR 	GENERAL TOLERANCES:	DRAWN BY & DATE GF 3-6-00	TITLE: MINI-C, RECEPTACLE, FEMALE, 5 POLE, 22 AWG., DEVICE NET		
CRITICAL 	3 PLACE ± .005 2 PLACE ± .01 ANGULAR ± 2°	CHECKED BY & DATE DW 3-6-00			
SPC 	Util-Mate CAGE CODE 58967	APPROVED BY & DATE DW 3-6-00	MOLEX INCORPORATED Orange, CA 92868		
			PART NO. SEE CHART	DRAWING NO. SD-84915-0076	SHEET NO. 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.					REV B