

C. Westcott 12-2-92
 APPROVED/DATE
 1
 REV

SAFETY ORGANIZATION(S)

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET:

- UL RECOGNIZED
- CSA CERTIFIED
- VDE APPROVED
- SEV PENDING

- UL 544
- CSA 22.2, NO. 0, 0.4, B
- VDE 0565-3

OPERATING SPECIFICATIONS:

- LINE VOLTAGE/CURRENT, 15 AMP., 120/250 VAC
- 50-60Hz
- LINE FREQUENCY, 12 AMP., 120V 60 Hz
- MAX. CASE RISE & RATED CURRENT, 50°C
- MAX. LEAKAGE CURRENT, EACH LINE TO GROUND, 2mA @ 120V 60 Hz
- OPERATING AMBIENT TEMP. RANGE, -10°C TO +40°C @ RATED CURRENT, I_r
- IN AN AMBIENT, T_a, HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_o, IS AS FOLLOWS:

$$I_o = I_r \sqrt{\frac{85 - T_a}{45}}$$

RELIABILITY SPECIFICATIONS:

- STORAGE TEMPERATURE, -40°C TO +85°C
- HUMIDITY, 21 DAYS @ 40°C 95% RH
- CURRENT OVERLOAD TEST, 5 TIMES RATED CURRENT FOR 8 SECONDS

TEST SPECIFICATIONS:

- INDUCTANCE, 5.07 mH NOMINAL
- CAPACITANCE, (MEASURED @ 1 KHz, 0.25 VAC MAX., 25°C ±1°C) 2.07µF ±20%
- LINE TO LINE, 165 KΩ
- DISCHARGE RESISTOR 6000 MΩ (MIN) AT 100 VDC
- LINE/GROUND AND LINE/LINE 20°C AND 50% RH
- INSULATION RESISTANCE (W/O DISCHARGE RESISTOR)

RECOMMENDED RECEIVING INSPECTION HIPOIT:

- LINE TO GROUND, 2250 VDC FOR 1 MINUTE
- LINE TO LINE, 1450 VDC FOR 1 MINUTE

FILTER APPROVAL, THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.

TOLERANCE EXCEPT AS NOTED


DECIMAL, .XXX .XX .X ANGLES ± 1°
 ENGLISH, ±.025
 METRIC, ±

MATERIAL:

AS SUPPLIED

FINISH:

AS SUPPLIED



50Ω - 50Ω (MINIMUM) INSERTION LOSS

FREQUENCY MHz	.01	.03	.05	.07	.1	.15	.3	.5	1	2	5	10	20	30
COMMON	4	13	18	21	24	27	35	41	34	22	12	5	2	
DIFF.	12	19	15	13	24	51	70	70	70	70	70	70	65	55

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.



POWER LINE FILTER

SCALE DATE 17-21-92
 NTS
 DRG. NO. 15EHT6.01
 DRG. BY CFW
 CFW

