

			DESIGNED FOR USE WITH RG-141/U CABLE		REVISIONS																																																
			CABLE ENTRY DIAMETER MINIMUM		REV	DESCRIPTION	DATE	APPROVED																																													
			COLLAR CONTACT SLOT		.120 .040	021	REVISED	DAC 6/15/99	DCM 6/16/99																																												
<table><thead><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr></thead><tbody><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.1</td><td>Temperature Rating -65°C To +125°C</td></tr><tr><td>Frequency Range (GHz) DC to 12.4</td><td>Recommended Mating Torque 7-10 in-Lbs</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 250</td><td>Mating Characteristics:</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR 1.10 ±.005 f(GHz)</td><td>Insertion (MAX Lbs) N/A</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, except high temp shall be +85°C</td></tr><tr><td>Insertion Loss (dB MAX) .08 √f(GHz)</td><td>Withdrawal (MIN Oz) N/A</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>RF Leakage (dB MIN) -[60-f(GHz)]</td><td>Force to Engage and Disengage (In-Lbs MAX) 2</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000</td><td>Axial (Lbs) 6.0</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Radial (In-Oz) 4.0</td><td></td></tr><tr><td>Center Contact 2.0</td><td>Cable Retention</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial Force (Lbs) 30 Min</td><td></td></tr><tr><td>Cable to Housing 0.5</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670</td><td></td><td></td></tr><tr><td>I.R.(Megohms MIN) 10,000</td><td></td><td></td></tr></tbody></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C To +125°C	Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 7-10 in-Lbs	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I	VSWR 1.10 ±.005 f(GHz)	Insertion (MAX Lbs) N/A	Thermal Shock MIL-STD-202, Method 107, Condition B, except high temp shall be +85°C	Insertion Loss (dB MAX) .08 √f(GHz)	Withdrawal (MIN Oz) N/A	Moisture Resistance MIL-STD-202, Method 106	RF Leakage (dB MIN) -[60-f(GHz)]	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000	Axial (Lbs) 6.0		Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0		Center Contact 2.0	Cable Retention		Outer Contact 2.0	Axial Force (Lbs) 30 Min		Cable to Housing 0.5	Torque (In-Oz) N/A		RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670			I.R.(Megohms MIN) 10,000			HOUSING COUPLING NUT CLAMP NUT CAP		STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303		PASSIVATE PER ASTM A380	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																			
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C To +125°C																																																			
Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 7-10 in-Lbs	Vibration MIL-STD-202, Method 204, Condition D																																																			
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I																																																			
VSWR 1.10 ±.005 f(GHz)	Insertion (MAX Lbs) N/A	Thermal Shock MIL-STD-202, Method 107, Condition B, except high temp shall be +85°C																																																			
Insertion Loss (dB MAX) .08 √f(GHz)	Withdrawal (MIN Oz) N/A	Moisture Resistance MIL-STD-202, Method 106																																																			
RF Leakage (dB MIN) -[60-f(GHz)]	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																			
Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation																																																				
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000	Axial (Lbs) 6.0																																																				
Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0																																																				
Center Contact 2.0	Cable Retention																																																				
Outer Contact 2.0	Axial Force (Lbs) 30 Min																																																				
Cable to Housing 0.5	Torque (In-Oz) N/A																																																				
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670																																																					
I.R.(Megohms MIN) 10,000																																																					
DIELECTRIC		TFE FLUOROCARBON PER ASTM-D-1457		N/A																																																	
CENTER CONTACT COLLAR		BRASS PER ASTM-B-16, HALF HARD		GOLD PLATE PER MIL-G-45204																																																	
RETAINING RING		BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H		N/A																																																	
GASKET		SILICONE RUBBER PER ZZ-R-765		N/A																																																	
COMPONENT		MATERIAL		FINISH																																																	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°		DRAWN BY R.N.L. DATE 7-26-74 CHECKED BY RMF 8-1-74 APPD BY R.B. 8-1-74		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																	
These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		USE ASS'Y PROCEDURE 408-04965 NO. AP. (20-077)		TITLE OSM RIGHT ANGLE CABLE PLUG CLAMP ATTACHMENT																																																	
		SIZE B		CODE IDENT NO. 26805	2007-7141-02	REV 021																																															
		SCALE 5:1		SHEET 1 OF 1																																																	