

NOTES:

1. MATERIALS AND FINISHES:

BODY, WASHER, BRAID CLAMP & HEX NUT - BRASS (ASTM-B16 H02, C36000), WHITE BRONZE PLATING
 CONTACT PIN - BRASS, GOLD PLATING (.000030 MIN) THICK
 INSULATOR - PTFE PER ASTM D 1710 OR EQUIV.
 GASKET - SILICONE RUBBER, COLOR RED

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM
 B. FREQUENCY RANGE: DC - 11 GHz

3. MECHANICAL:


A. TEMPERATURE RANGE: -65° C TO +165° C

4. PACKAGING:


A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 *AMPHENOL, 31-6148, AND DATE CODE

5. CRIMPED CONTACT PIN = HEX CRIMP SIZE .100 IN

31-6148		REVISIONS			
DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ.	A	RELEASE TO MFG.	8/29/06	46221	CPM/



RECOMMENDED CABLE STRIPPING DIMS



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
 ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL	DRAWN C. McGRATH ENGINEER	DATE 4/4/05	TITLE TNC CLAMP PLUG (FOR RG-58C/U, 58/U, 142A/U, 223/U CABLE)	Amphenol Amphenol Corporation RF/Microwave Operations Danbury, Conn. U.S.A. 06810	
REFERENCE	APPROVED Q. BARTHELMES	DATE 8/25/06	CODE ID 74868	DWG SIZE B	DRAWING NO. 31-6148
CAD FILE H:\DEPT611\TNC\031\ASSY\6148			SCALE: 2:1 SHEET OF		ISSUE A