

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

SUGGESTED MATING TAB

SHOULDER MAY BE ELIMINATED IF NOT FEASIBLE

11.30 [.445] MIN CLEARANCE

1.02 [.040] / 0.76 [.030]

0.25 [.010] MAX CUT-OFF

8.25 [.325] MIN

6.43 [.253] / 6.27 [.247]

2.03 [.080] DIA HOLE / 1.65 [.065]

1.14 [.045] / 0.89 [.035] x 45°

3.48 [.137] / 3.33 [.131]

4.72 [.186] / 4.32 [.170]

8.05 [.317] / 7.80 [.307]

0.84 [.033] / 0.79 [.031]

0.13 [.005] R MAX BOTH SIDES

10° ±2'

1 - MATL: 1/2H BRASS OR NICKEL PL STEEL.

2 - NO BURRS PERMISSIBLE AT HOLE.

3 - MUST BE FLAT WITHIN 0.076 [.003] OVER THIS LENGTH.

4 - TIN PLATING IS REQUIRED ON BRASS WHEN TERMINAL TEMP. IS OVER 225°F

5 - HOLE MUST BE SYMMETRICAL ABOUT TAB Q. WITHIN 0.076 [.003]
* TO BE USED ONLY WHEN SHOULDER IS ELIMINATED.

1 FOR USE WITH MKII POSITIVE LOCK, LOW INSERTION FORCE FASTON RECEPTACLES AND MOST BUDGET FASTON RECEPTACLES.

2 PRELIMINARY - NOT FOR PRODUCTION

3 PREPRODUCTION - FASR REQUIRED

4 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

5 HOUSING MATERIAL MEETS MINIMUM GLOW WIRE FLAMMABILITY INDEX OF 850°C PER IEC 60695-2-12 AND MINIMUM GLOW WIRE IGNITION TEMPERATURE OF 775°C PER IEC 60695-2-13.

6 NYLON, GWT 750°C.

.860

.362
2 PLC

1.080 REF

.380

.362
2 PLC

.290 REF

.595

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
G	01	P11 REVISED PER ECO-13-016534	22OCT13	JR	PD

.040

±.015
1.135

6 NYLON V0, NATURAL	2-520935-4
66 NYLON V0, NATURAL	2-520935-3
6 NYLON V2 RED	2-520935-2
6 NYLON V2 NATURAL	2-520935-1
4 OBSOLETE	
V0 GREEN	1-520935-9
V0 BLACK	1-520935-8
V0 BROWN	1-520935-7
V0 YELLOW	1-520935-6
V0 BLUE	1-520935-5
V0 RED	1-520935-2
V0 NATURAL	1-520935-1
BLACK	520935-8
BROWN	520935-7
YELLOW	520935-6
BLUE	520935-5
GREEN	520935-4
WEATHER RESIST BLACK	520935-3
RED	520935-2
NATURAL	520935-1
COLOR	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	4/14/88	 TE Connectivity	
DIMENSIONS: INCHES		CHK	M FEHER	4/14/88		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	R KUZO	4/14/88		
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .010 4 PLC ± - ANGLES ± -		PRODUCT SPEC	NAME			
MATERIAL: 6/6 NYLON		FINISH	SEE TABLE		APPLICATION SPEC	
WEIGHT		-		SIZE	A2	
CUSTOMER DRAWING		SCALE	4:1		CAGE CODE	00779
SCALE		4:1		DRAWING NO	C=520935	
SHEET		1 of 1		RESTRICTED TO	-	
REV		P11				

1471-9 (3/11)