

PCB plug-in socket, 6 contacts (2 NO, lamp socket)

5.05.510.645/0000

For soldering onto PCBs. Additional fixing of the PCBs is not required. Solder terminals for PCB 3.5 mm long, for 1.3 mm hole.



Dimensions

| | |
|------------------|--------------|
| Size not mounted | 22 mm |
| Length | 22 mm |
| Width | 24 mm |
| Height | 10.5/14.5 mm |
| Mounting depth | 47 mm |
| Mounting depth | 47 mm |

Other specifications

| | |
|--|--|
| Contacts | 6 |
| Shock resistance acc. to IEC 60068-2-27 | amplitude < 50g, 11ms, half sinusoidal |
| Contact arrangement | 2 NO, lamp socket |
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating max. with lamp /LED | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Hot wire ignition acc. to IEC 60695-2-1 | yes |
| Resistance to vibrations acc. to IEC 60068-2-6 | 10 g at 20 ... 500 Hz |
| ROHS compliant | yes |
| REACH compliant | yes |

