


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
24E1	24.0	.035	.160	2.01	8,000	C-2F
24B1	24.0	.040	.239	3.00	4,000	C-2F
24C1	24.0	.072	.278	3.49	6,000	C-2V
35A1	35.0	.040	.239	3.00	7,500	C-2F
48D1	48.0	.021	.160	2.01	20,000	CC-2F
55C1	55.0	.050	.478	6.01	5,000	CC-2F

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED  
 1 PL +/- 0.2  
 2 PL +/- 0  
 ANGLE +/- 0

**JKL** COMPONENTS CORPORATION

TITLE  
 T-2 TELEPHONE SLIDE BASE ANSI #1

DRAWN BY  
 L. WENGSTROM

APPVD BY DATE  
 S.C. 4/11/07

SIZE  
**A**

FSCM NO.  
**55335**

DRAWING NO.

**SLIDE BASE ANSI #1**

REV. NO. DESCRIPTION/ECO NUMBER

APPVD DATE

SCALE  
 NONE

RELEASED DATE  
 8/16/00

REVISION DATE  
 4/11/07

REV. NO. **A**

SHEET 1 OF 1

- CAD DRAWING -  
 MANUAL REVISIONS NOT PERMITTED