


Printed-circuit board connector - MCV 0,5/ 8-G-2,5 GY SO - 1700991

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 4 A, number of positions: 8, pitch: 2.5 mm, color: gray, contact surface: Tin, mounting: Wave soldering




The figure shows a 10-position version of the product

Your advantages

- Well-known mounting principle allows worldwide use
- Vertical connection enables multi-row arrangement on the PCB



Key Commercial Data

Packing unit	50 pc
GTIN	 4 046356 508681
GTIN	4046356508681

Technical data

Dimensions

Length [l]	8.1 mm
Width	21.9 mm
Pitch	2.5 mm
Dimension a	17.5 mm
Width [w]	21.9 mm
Height [h]	13.6 mm
Height	10.1 mm
Length of the solder pin	3.5 mm
Pin dimensions	0.8 x 0.8 mm
Length	8.1 mm

General

Range of articles	MCV 0,5/...-G
-------------------	---------------

Printed-circuit board connector - MCV 0,5/ 8-G-2,5 GY SO - 1700991

Technical data

General

Rated voltage (III/3)	80 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	4 A
Color	gray
Number of positions	8

Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>