




PRODUCT NUMBER SEE SHEET 2




spec ref	*	dr	Peng-Bing Fu	2012/07/29	projection	MM	size	A3	scale	3:2
tolerance std	ASME Y14.5	eng	Peng-Bing Fu	2012/11/14	chr	Tian-Xu Huang	2012/11/15	ecn no	ELX-DG-013144-1	
		appr	Pei-Ming Zheng	2012/11/15	product family	PwrBlade+	rel level	Released		
surface	✓	linear	0.X	±0.5	FCI	4HP	dwg no	10106126-4000001	rev	B
			0.XX	±0.25		RA STB RECEPTACLE				
			0.XXX	±0.10						
ASME Y14.5	angular	0°	±2°	www.fci.com	cat. no.	Product - Customer Drw	sheet 1 of 3			

PRODUCT NO.	ROWS	HIGH POWER					
		E1	P4	P3	P2	P1	E2
10106126-4000001LF	D C B A		H3	H3	H3	H3	

CODE	DESCRIPTION
H3	STD HIGH POWER CONTACT(3.43)
HA	METAL HOLD DOWN



dr	Peng-Bing Fu	2012/07/29		projection		size	A3	scale	3:2	
eng	Peng-Bing Fu	2012/11/14					ecn no	ELX-DG-013144-1		
chr	Tian-Xu Huang	2012/11/15						rel level		
appr	Pei-Ming Zheng	2012/11/15	product family			PwrBlade+	Released			
	title	4HP				dwg no	10106126-4000001		rev	
		RA STB RECEPTACLE							B	
www.fci.com	cat. no.		Product - Customer Drw				sheet 2 of 3			





Copyright FCI.

NOTES:

- 1) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
 - HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-0.
 - SIGNAL CONTACT - COPPER ALLOY.
 - POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION REFER TO FCI 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15 ± 0.025 MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn
OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 ± 0.07 MM HOLE.
- 8) PRODUCT SPECIFICATION REFER TO FCI GS-12-658.
APPLICATION SPECIFICATION REFER TO FCI GS-20-141.
PRODUCT PACKAGED IN TRAYS, REFER TO FCI GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL
MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE
MAY BE DIFFERENT FOR OPTIMIZE THE MOLDING PROCESS. THE
VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.
- 10) A  SYMBOL WILL BE NEXT TO ANY DIMENSION,VIEW,OR NOTE WHICH
HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.



Copyright FCI.

dr	Peng-Bing Fu	2012/07/29	projection 	MM 	size	A3	scale	3:2
eng	Peng-Bing Fu	2012/11/14			ecn no			ELX-DG-013144-1
chr	Tian-Xu Huang	2012/11/15			rel level			Released
appr	Pei-Ming Zheng	2012/11/15	product family		PwrBlade+			
	title 4HP RA STB RECEPTACLE				dwg no 10106126-4000001	rev B		
www.fci.com	cat. no.		Product - Customer Drw			sheet 3 of 3		