



## Product: [8794](#)

Electronic, 3 C #22 Sol BC, PO Ins, PVC Jkt, CM

 [Request Sample](#)

### Product Description

Electronic, 3 Conductor 22AWG (Solid) Bare Copper, PO Insulation, PVC Outer Jacket, CM

### Technical Specifications

#### Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
22	Solid	BC - Bare Copper	0.026 in	3

Conductor Count: 3

##### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.018 in

##### Color Chart

Number	Color
1	Green
2	Red
3	Yellow

##### Outer Shield Material

Material
No Shield

##### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.178 in	0.022 in

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR
16 Ohm/1000ft

##### Capacitance

Nom. Capacitance Conductor to Conductor
16 pF/ft

##### Inductance

Nominal Inductance
0.22 $\mu$ H/ft

## Delay

Nominal Velocity of Propagation (VP) [%]
66 %

## Current

Max. Recommended Current [A]
3 Amps per conductor @ 25°C

## Voltage

UL Voltage Rating
300 V RMS

## Temperature Range

UL Temp Rating:	60°C (UL AWM Style 2093)
Operating Temp Range:	-30°C To +60°C

## Mechanical Characteristics

Bulk Cable Weight:	21 lbs/1000ft
Max Recommended Pulling Tension:	23 lbs
Min Bend Radius/Minor Axis:	2 in

## Standards

NEC/(UL) Specification:	CM
UL AWM Style:	UL Style 2093 (300 V 60°C)

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
8794 6061000	Gray, Rose	Reel	1,000 ft	612825216520
8794 606U1000	Gray, Rose	UnReel	1,000 ft	612825216513

Footnote: C - CRATE REEL PUT-UP.

## History

Update and Revision:	Revision Number: 0.299 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and

regulations based on their individual usage of the product.