
RAFIX 22 FSR - Emergency stop pushbutton, metal mushroom (aluminium anodized), illuminated 1.30.283.111/0300

| General information | |
|--------------------------------------|--|
| Form of lens | conical mushroom form |
| Color of lens | red |
| Form of collar | round |
| | |
| Dimensions | |
| Mushroom Diameter | 37.5 mm |
| Overall height | 41.1 mm |
| Mounting hole | 22.3 mm |
| Key grid | 40 x 40 mm |
| Mechanical design | |
| Mounting | Metal threaded rings |
| Contact function | latching |
| Reset | by pulling |
| Illuminability | yes, window white |
| Torque for nut ring | 1.2 Nm |
| Mechanical characteristics | |
| Robustness max. | 100 N |
| Other specifications | |
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Ambient temp. operating min. | -40 °C |
| · · · · | -40 ℃ +85 ℃ |
| Ambient temp. operating max. | |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental restistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Salt spray | IEC 600 68-2-11 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out to IEC 60947-5-1



Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.



