

RAFIX 22 FSR - Emergency stop pushbutton, metal mushroom (aluminium anodized), illuminated
1.30.283.111/0300

General information

| | |
|----------------|-----------------------|
| Form of lens | conical mushroom form |
| Color of lens | red |
| Form of collar | round |

Dimensions

| | |
|-------------------|------------|
| Mushroom Diameter | 37.5 mm |
| Overall height | 41.1 mm |
| Mounting hole | 22.3 mm |
| Key grid | 40 x 40 mm |

Mechanical design

| | |
|---------------------|----------------------|
| Mounting | Metal threaded rings |
| Contact function | latching |
| Reset | by pulling |
| Illuminability | yes, window white |
| Torque for nut ring | 1.2 Nm |

Mechanical characteristics

| | |
|-----------------|-------|
| Robustness max. | 100 N |
|-----------------|-------|

Other specifications

| | |
|--------------------------------------|--|
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Ambient temp. operating min. | -40 °C |
| Ambient temp. operating max. | +85 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Salt spray | IEC 600 68-2-11 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out to IEC 60947-5-1



