







NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
1	INSULATOR		1	LCP		COLOR:BLACK
2	CONTACT		N	COPPER ALLOY		Au



MOUNTING LAYOUT

ROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

極数 NO. OF POS.	A	B	D
10	1.6	4.1	3.2
16	2.8	5.3	4.4
20	3.6	6.1	5.2
24	4.4	6.9	6.0
26	4.8	7.3	6.4
30	5.6	8.1	7.2
34	6.4	8.9	8.0
40	7.6	10.1	9.2
44	8.4	10.9	10.0
50	9.6	12.1	11.2
54	10.4	12.9	12.0
60	11.6	14.1	13.2
64	12.4	14.9	14.0
70	13.6	16.1	15.2
80	15.6	18.1	17.2

注記
NOTE

1. 型番
P/N 20 5805 XXX 00X 829 H +
極数
NO. OF POS.
バリエーション
VARIATION

	ANCHOR PLATE	BOSS	GUIDE POST
0	-	-	-
1	-	◎	-

◎:WITH -:WITHOUT

② テール及び金具底面の相互の輪郭度は、0.1MAX.
COPLANARITY OF CONTACT TAIL AND
ANCHOR PLATE IS 0.1MAX.

③ 凸凹無き事。
FLAT KEEPING AREA

TOLERANCE / 一般公差 (S)		PRODUCT SPEC / 製品規格							
X < 10 ±0.2				A		DCN-977		10-31-07	
10 ≤ X < 30 ±0.25		UNIT		O		EDN-890		8-09-06	
30 ≤ X ±0.3		mm		NO.		EDN/DCN		DATE	
ANGLE / 角度		SCALE		DATE		ISSUE		CHECKED	
±3°		3/1		8-09-06		APPROVED		APPROVED	
DRAWN		DESIGNED		CHECKED		APPROVED		PART NAME / 品名	
T. KOMATSU		A. TSUNEMURA		Y. SHIROYAMA		N. HAYASHI		SERIES 5805 REC ASSY ST SMT	
KYOCERA		KYOCERA ELCO CORPORATION		DWG NO. / 図番		ISHEET/REV		0.4mm PITCH BOARD TO BOARD H=1.0 (LCP)	
				BJ5 5805033		1/1		A	