

**Product:** [735A1P](#) 



DS-3 and DS-4, 735\* Series, #26-1 SPC Coax, CMP

## Product Description

26 AWG solid .016" silver-plated copper conductor(s), plenum, foam FEP insulation, Beldfoil®; tinned copper braid shield (95% coverage), Flamarrest® jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material                             | Nominal Diameter | No. of Coax |
|-----|-----------|--------------------------------------|------------------|-------------|
| 26  | Solid     | SCCS - Silvered Copper Covered Steel | 0.016 in         | 1           |

Conductor Count: 1

#### Insulation

| Material                                    | Nominal Diameter |
|---------------------------------------------|------------------|
| FEP - Fluorinated Ethylene Propylene (Foam) | 0.077 in         |

#### Outer Shield Material

| Type  | Layer | Material           | Material Trade Name | Coverage [%] |
|-------|-------|--------------------|---------------------|--------------|
| Tape  | 1     | Alum / Poly        | Beldfoil®           | 100%         |
| Braid | 2     | Tinned Copper (TC) |                     | 93%          |

#### Outer Jacket Material

| Material                                | Material Trade Name | Nominal Diameter |
|-----------------------------------------|---------------------|------------------|
| PVC-LS - Polyvinyl Chloride (Low Smoke) | Flamarrest®         | 0.129 in         |

### Electrical Characteristics

#### Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR Conductor Resistance | Nominal Inner Shield DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|--------------------------------------------|--------------------------|--------------------------|---------------------|
| 41 Ohm/1000ft         | 41 Ohm/1000ft                              | 5.3 Ohm/1000ft           | 5.3 Ohm/1000ft           | 5.3 Ohm/1000ft      |

#### Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 17.7 pF/ft                           |

#### Inductance

| Nominal Inductance |
|--------------------|
| 0.097 µH/ft        |

#### Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 75 Ohm                           |

#### Return Loss (RL)

| Frequency [MHz] | Minimum Return (RL) |
|-----------------|---------------------|
| 15-95 MHz       | 30 dB               |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|------------------------------------------|
| 1.34 ns/ft    | 76%                                      |

High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) |
|-----------------|-----------------------------------|
| 1 MHz           | 0.6 dB/100ft                      |
| 1.024 MHz       | 0.61 dB/100ft                     |
| 4.224 MHz       | 1.1 dB/100ft                      |
| 5 MHz           | 1.2 dB/100ft                      |
| 10 MHz          | 1.7 dB/100ft                      |
| 17.184 MHz      | 2.2 dB/100ft                      |
| 22.368 MHz      | 2.5 dB/100ft                      |
| 25.92 MHz       | 2.7 dB/100ft                      |
| 44.736 MHz      | 3.6 dB/100ft                      |
| 50 MHz          | 3.8 dB/100ft                      |
| 69.632 MHz      | 4.5 dB/100ft                      |
| 77.76 MHz       | 4.8 dB/100ft                      |
| 100 MHz         | 5.5 dB/100ft                      |
| 137.088 MHz     | 6.4 dB/100ft                      |
| 200 MHz         | 7.8 dB/100ft                      |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

Temperature Range

|                       |              |
|-----------------------|--------------|
| Operating Temp Range: | 0°C To +75°C |
|-----------------------|--------------|

Mechanical Characteristics

|                             |               |
|-----------------------------|---------------|
| Bulk Cable Weight:          | 18 lbs/1000ft |
| Max. Pull Tension:          | 25 lbs        |
| Min Bend Radius/Minor Axis: | 0.9 in        |

Standards

|                       |                                     |
|-----------------------|-------------------------------------|
| NEC/(UL) Compliance:  | CMP                                 |
| CEC/C(UL) Compliance: | CMP                                 |
| RG Type:              | Mini 59/U Type                      |
| Other Compliance:     | Telcordia Specification GR-139-CORE |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| Environmental Space:                  | Indoor - Plenum               |
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/11/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2006-04-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LS0H, Toxicity Testing

|                    |           |
|--------------------|-----------|
| UL Flammability:   | NFPA 262  |
| CSA Flammability:  | FT6       |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

|               |     |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Part Number

|                    |       |
|--------------------|-------|
| Non-Plenum Number: | 735A1 |
|--------------------|-------|

Variants

| Item #         | Color | Putup Type | Length   | UPC          |
|----------------|-------|------------|----------|--------------|
| 735A1P 008500  | Gray  | Reel       | 500 ft   | 612825184706 |
| 735A1P 0081000 | Gray  | Reel       | 1,000 ft | 612825184690 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.153 Revision Date: 04-02-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.