

RAFIX 16 - Signal indicator, round lens

1.65.124.021/1306

Legending can only be made externally on a label holder.



General information

| | |
|----------------|-----------------|
| Form of lens | lens round |
| Color of lens | transparent red |
| Form of collar | round |

Dimensions

| | |
|-------------------|----------------|
| Collar dimensions | ø 24.95 mm |
| Overall height | 6.95 mm |
| Mounting depth | 30.5 / 44.7 mm |
| Mounting hole | 16.2 mm |
| Key grid | 25 x 25 mm |

Mechanical design

| | |
|--------------|----------|
| Mounting | ring nut |
| Illumination | yes |

Mechanical characteristics

| | |
|-----------------|-------|
| Robustness max. | 100 N |
|-----------------|-------|

Other specifications

| | |
|---|--|
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Operation temperature min. | -25 °C |
| Ambient temp. operating max. without lamp / LED | +70 °C |
| Ambient temp. operating max. with lamp /LED | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out



