

Cable gland - G-INSEC-M12-S68N-NCRS-S - 1411187

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 3 mm ... 6.5 mm, Shielding: Yes, Connecting thread: M12, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	14.0 GRM
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	28 mm
Length without connecting thread	22 mm
Connecting thread diameter	12 mm
Wrench size, union nut	14 mm
Wrench size, support	14 mm
Hexagon angular dimension GRP	15.5 mm
Length of the connecting thread	6 mm
External cable diameter	3 mm ... 6.5 mm

Ambient conditions

Degree of protection	IP68
----------------------	------

Cable gland - G-INSEC-M12-S68N-NCRS-S - 1411187

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

General

Cable gland material	Brass, nickel-plated
Seal material	CR/NBR
Cable seal material	CR
O-ring material	NBR
Shielded	Yes
Thread type on connection side	M12
Torque	6 Nm ... 8 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

Cable gland - G-INSEC-M12-S68N-NCRS-S - 1411187

Approvals

UL Recognized 

Drawings

Dimensional drawing

