

Cable gland - G-INSEC-PG42-L68N-NNES-S - 1411203

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 30 mm ... 38 mm, Shielding: Yes, Connecting thread: Pg42, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	60 mm
Length without connecting thread	48 mm
Connecting thread diameter	54 mm
Wrench size, union nut	58 mm
Wrench size, support	58 mm
Hexagon angular dimension GRP	64 mm
Length of the connecting thread	12 mm
External cable diameter	30 mm ... 38 mm

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 100 °C

Cable gland - G-INSEC-PG42-L68N-NNES-S - 1411203

Technical data

General

Cable gland material	Brass, nickel-plated
Seal material	CR
Cable seal material	CR
O-ring material	NBR
Shielded	Yes
Thread type on connection side	Pg42
Torque	40 Nm ... 50 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted


Approval details

UL Recognized 

Cable gland - G-INSEC-PG42-L68N-NNES-S - 1411203

Drawings

Dimensional drawing



Phoenix Contact 2015 © - all rights reserved
<http://www.phoenixcontact.com>