



"P" INDICATES FOR MALE CAPS

SECTION-AA

FCI LOGO

**NOTE:**

- 1: MATERIAL  
UL APPROVED POLYPROPYLENE RED/BLACK COLOUR
- 2: PACKAGING  
PRIMARY PACKING 100 NOS IN POLYETHYLENE BAG

"This LF product meets European Union Directives and other country regulations as described in GS-22-008"  
Packaging as per GS-14-920

SHELL SIZE	PART NO: RED COLOUR	PART NO: BLACK COLOUR	A ±0.3		B ±0.3		D ±0.2		E ±0.2		F TOP	F BOTTOM
			F ±0.1									
50	P	70522CLF	70522BLF	56.0	15.9	54.0	4.5	12.10	12.15			
	S	70527CLF	70527BLF	55.2	14.5	52.4	5.0	10.50	10.35			
37	P	70521CLF	70521BLF	59.0	13.0	56.7	4.5	8.70	9.00			
	S	70526CLF	70526BLF	57.3	11.8	54.7	5.0	7.40	7.50			
25	P	70520CLF	70520BLF	42.0	13.2	40.0	4.5	8.98	9.00			
	S	70525CLF	70525BLF	40.9	11.8	38.3	5.0	7.65	7.70			
15	P	70519CLF	70519BLF	28.1	13.0	26.0	4.5	8.98	9.00			
	S	70524CLF	70524BLF	27.0	11.8	24.6	5.0	7.65	7.70			
09	P	70518CLF	70518BLF	20.3	13.0	17.7	4.5	8.98	9.00			
	S	70523CLF	70523BLF	18.5	11.8	16.2	5.0	7.65	7.70			

mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection		product family D-SUB			
REF NOTE				tolerances unless otherwise specified		angles linear		MM		title			
A	I06-0160	GVJ	2006/08/18	±0.1		0°±1°		scale -		D-SUB DUST CAP STANDARD			
B	I09-0015	AMR	2008/01/18							dwg no		sheet 1 of 1	size
C	I09-0025	AMR	2009/02/14							C-DSUB-0157		A4	
sheet index				revision		c		type		PRODUCT CUSTOMER Drawing			
1				1									



FCIconnect.com

Copyright FCI